		CORPORATION	Revision nr. 1 Dated 3/5/2021
			First compilation
C1030 - Carbo	ol-Fuchsi	n (Ziehl-Neelsen)	Printed on 3/5/2021
		· · · ·	Page n. 1/18
		fety Data Sheet ig to U.S.A. Federal Hazcom 2012	
1. Identification			
1.1. Product identifier Code:	C1030		
Product name		l-Fuchsin (Ziehl-Neelsen)	
1.2. Relevant identified uses of the substand Intended use For laboratory		and uses advised against	
1.3. Details of the supplier of the safety data	ı sheet		
Name Full address District and Country	EXAX 14325 33760	DL CHEMICAL CORPORATION 60 TH ST N CLEARWATER - FLORIDA	
	US Tol 1	797 594 7799	
		727-524-7732 727-532-8221	
e-mail address	i ux i		
	info@	exaxol.com	
1.4. Emergency telephone number For urgent inquiries refer to		255-3924 Fel Inc.	
2. Hazards identification			
1. Classification of the substance or mixture)		
ne product is classified as hazardous pursuant oduct thus requires a safety datasheet. ny additional information concerning the risks fo			ication Standard (HCS) (29 CFR 1910.1200). Th 11 and 12 of this sheet.
assification and Hazard Statement			
azard pictograms:			
Flammable liquid, category 2		Highly flammable liquid and vapour.	
Carcinogenicity, category 1A		May cause cancer.	
Germ cell mutagenicity, category 2		Suspected of causing genetic defects.	
Specific target organ toxicity - repeated exposu	ire, category 2	May cause damage to organs through prolonged or	
		repeated exposure. Causes severe skin	



C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Dispose of contents / container to an approved waste disposal plant.

Hazard statements:

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements:

Prevention: P273

Avoid release to the environment.

Response:

Storage:

Disposal: **P501**

Additional hazards

Auullional nazarus

Information not available

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	Conc. %	Classification:
WATER		
CAS 7732-18-5	84.7	
EC 231-791-2		
INDEX -		
ETHANOL		
CAS 64-17-5	9	Flammable liquid, category 2 H225, Carcinogenicity, category 1A H350
EC 200-578-6		
INDEX 603-002-00-5		
PHENOL		
CAS 108-95-2	5	Germ cell mutagenicity, category 2 H341, Acute toxicity, category 3 H301, Acute toxicity, category 3 H311, Acute toxicity, category 3 H331, Specific target organ toxicity - repeated exposure, category 2 H373, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Hazardous to the aquatic environment, chronic toxicity, category 2 H411
EC 203-632-7		
INDEX 604-001-00-2		
Basic Fuchsin		
CAS 569-61-9	0.3	Carcinogenicity, category 1B H350
EC 209-321-2		
INDEX -		
METHANOL		
CAS 67-56-1	0.2	Flammable liquid, category 2 H225, Acute toxicity, category 3 H301, Acute toxicity, category 3 H311, Acute toxicity, category 3 H331, Specific target organ toxicity - single exposure, category 1 H370
EC 200-659-6		
INDEX 603-001-00-X		
4-METHYLPENTAN-2-ONE		

Revision nr. 1 Dated 3/5/2021

First compilation

Printed on 3/5/2021

Page n. 3/18

Revision nr. 1

Dated 3/5/2021 First compilation

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Printed on 3/5/2021 Page n. 4/18

CAS 108-10-1

0.2

Flammable liquid, category 2 H225, Carcinogenicity, category 2 H351, Acute toxicity, category 4 H332, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H335

EC 203-550-1 INDEX 606-004-00-4

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Revision nr. 1

Dated 3/5/2021 First compilation

Printed on 3/5/2021

Page n. 5/18

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2018

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Revision nr. 1

Dated 3/5/2021 First compilation

Printed on 3/5/2021

Page n. 6/18

/pe	Je Country	TWA/8h		STEL/15min			
		mg/m3	ppm	mg/m3	ppm		
TLV-ACGIH	-			1884	1000		
OSHA	USA	1900	1000				
CAL/OSHA	USA	1.9	1				
NIOSH	USA	1900	1000				
PHENOL							
Threshold Limit Valu Type	Le Country	TWA/8h		STEL/15min			
Type	Country	mg/m3	ppm	mg/m3	ppm		
TLV-ACGIH	-	19.2	5	ilig/ilio	ppin		
OEL	EU	8	2	16	4	SKIN	
				10	4		
OSHA	USA	19	5			SKIN	
CAL/OSHA	USA	19	5			SKIN	
NIOSH	USA	19	5	60 (C)	15,6 (C)	SKIN	
4-METHYLPENTAN- Threshold Limit Valu							
Туре	Country	TWA/8h		STEL/15min			
		mg/m3	ppm	mg/m3	ppm		
TLV-ACGIH	-	82	20	307	75		
OEL	EU	83	20	208	50		
OSHA	USA	410	100				
CAL/OSHA	USA	205	50	300	75		
NIOSH	USA	205	50	300	75		
METHANOL							
Threshold Limit Valu Type	Le Country	TWA/8h		STEL/15min			
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Country	mg/m3	ppm	mg/m3			
					ppm 250		
TLV-ACGIH	-	262	200	328	250	OKINI	
OEL	EU	260	200			SKIN	
	USA	260	200				
OSHA	USA	260	200	325 (C)	1000 (C)	SKIN	
OSHA CAL/OSHA NIOSH	USA	260	200	325	250	SKIN	

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Revision nr. 1

Dated 3/5/2021 First compilation

Printed on 3/5/2021

Page n. 7/18

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited. If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear

open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Revision nr. 1 Dated 3/5/2021

First compilation

Printed on 3/5/2021

Page n. 8/18

9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

4-METHYLPENTAN-2-ONE

Reacts violently with: light metals.Attacks various types of plastic materials.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHANOL

Risk of explosion on contact with: alkaline metals, alkaline oxides, calcium hypochlorite, sulphur monofluoride, acetic anhydride, acids, concentrated hydrogen peroxide, perchlorates, perchloric acid, perchloronitrile, mercury nitrate, nitric acid, silver, silver nitrate, ammonia, silver oxide, ammonia, strong oxidising agents, nitrogen dioxide. May react dangerously with: bromoacetylene, chlorine acetylene, bromine trifluoride, chromium trioxide, chromyl chloride, fluorine, potassium tert-butoxide, lithium hydride, phosphorus trioxide, black platinum, zirconium (IV) chloride, zirconium (IV) iodide. Forms explosive mixtures with: air.

4-METHYLPENTAN-2-ONE

May react violently with: oxidising agents. Forms peroxides with: air. Forms explosive mixtures with: hot air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHANOL

Avoid exposure to: sources of heat, naked flames.

4-METHYLPENTAN-2-ONE

Avoid exposure to: sources of heat.

METHANOL

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Revision nr. 1 Dated 3/5/2021

First compilation

Printed on 3/5/2021

Page n. 9/18

Avoid exposure to: heat, flames and sparks.

10.5. Incompatible materials

4-METHYLPENTAN-2-ONE

Incompatible with: oxidising substances, reducing substances.

METHANOL

Incompatible with: acid chlorides, acid anhydrides, oxidising agents, alkaline metals, reducing agents, acids.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological

effects of exposure to the product. 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Basic Fuchsin

LD50 (Oral) 5000 mg/kg Mouse

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Revision nr. 1 Dated 3/5/2021

First compilation

Printed on 3/5/2021

Page n. 10/18

ETHANOL

LD50 (Oral) > 5000 mg/kg Rat

LC50 (Inhalation) 120 mg/l/4h Pimephales promelas

4-METHYLPENTAN-2-ONE

LD50 (Oral) 2080 mg/kg Rat

LD50 (Dermal) > 16000 mg/kg Rabbit

LC50 (Inhalation) > 8,2 mg/l/4h Rat

PHENOL

LD50 (Oral) 282 mg/kg Rat

LD50 (Dermal) 660 mg/kg Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Suspected of causing genetic defects

CARCINOGENICITY

May cause cancer

Carcinogenicity Assessment: 64-17-5ETHANOL ACGIH:: A3 IARC:1 108-95-2PHENOL ACGIH:: A4 IARC:3 569-61-9Basic Fuchsin IARC:2B NTP: Reasonably Anticipated 108-10-14-METHYLPENTAN-2-ONE

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Revision nr. 1 Dated 3/5/2021

First compilation

Printed on 3/5/2021

Page n. 11/18

ACGIH:: A3 IARC:2B

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment. **12.1. Toxicity**

Information not available

12.2. Persistence and degradability

METHANOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
ETHANOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
4-METHYLPENTAN-2-ONE	
Solubility in water	> 10000 mg/l
Rapidly degradable	
PHENOL	
Rapidly degradable 12.3. Bioaccumulative potential	
METHANOL	
Partition coefficient: n-octanol/water	-0.77
BCF	0.2

	AICAL CORPORATION	Revision nr. 1
		Dated 3/5/2021
		First compilation
C1030 - Carbol-	Fuchsin (Ziehl-Neelsen)	Printed on 3/5/2021
		Page n. 12/18
ETHANOL		
Partition coefficient: n-octanol/water	-0.35	
4-METHYLPENTAN-2-ONE		
Partition coefficient: n-octanol/water	1.9	
PHENOL		
Partition coefficient: n-octanol/water	1.47	
2.4. Mobility in soil		
4-METHYLPENTAN-2-ONE		
Partition coefficient: soil/water	2.008	
2.5. Results of PBT and vPvB assessment		

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, 3286 IATA:

14.2. UN proper shipping name

ADR / RID:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (ETHANOL; PHENOL)
IMDG:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (ETHANOL; PHENOL)
IATA:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (ETHANOL; PHENOL)

14.3. Transport hazard class(es)

Class: 3

ADR / RID:

Label: 3 (6.1,8)





	EXAX	OL CHEMICAL CORPORATION	Revision Dated 3/5 First com	5/2021
	C1030	- Carbol-Fuchsin (Ziehl-Neelser	Printed or	n 3/5/2021
	01000		Page n. 1	3/18
IMDG:	Class: 3	Label: 3 (6.1,8)		>
IATA:	Class: 3	Label: 3 (6.1,8)		>
4.4. Packing group			• • •	
ADR / RID, IMDG, IATA:	II			
4.5. Environmental	hazards			
ADR / RID:	NO			
IMDG:	NO			
IATA:	NO			
14.6. Special precaut	ions for user			
ADR / RID:		HIN - Kemler: 368	Limited Quantities: 1 L	Tunnel restriction code: (D/E)
		Special Provision: -	L	
IMDG:		EMS: F-E, S-C	Limited Quantities: 1 I	
IATA:		Cargo:	Maximum quantity: 5 L	Packaging instructions 363
		Pass.:	Maximum quantity: 1 L	Packaging instructions 352
				002

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

U.S. Federal Regulations

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

108-95-2 108-10-1 PHENOL (Phenols) 4-METHYLPENTAN-2-ONE

EXAXOL CHEMIC	Revision nr. 1	
		Dated 3/5/2021
		First compilation
C1030 - Carbol-Fue	chsin (Ziehl-Neelsen)	Printed on 3/5/2021
	(Page n. 14/18
		' '
67-56-1	METHANOL	
Clean Air Act Section 602 Class I Substances:		
No component(s) listed.		
Clean Air Act Section 602 Class II Substances:		
No component(s) listed.		
<u>Clean Water Act –</u>		
Priority Pollutants:		
108-95-2	PHENOL (Phenols)	
<u>Clean Water Act –</u>		
Toxic Pollutants:		
108-95-2	PHENOL (Phenols)	
DEA List I Chemicals (Precursor Chemicals):		
No component(s) listed.		
DEA List II Chemicals (Essential Chemicals):		
No component(s) listed.		
EPA List of Lists:		
313 Category Code:		
108-95-2	PHENOL (Phenols)	
108-10-1	4-METHYLPENTAN-2-ONE	
67-56-1	METHANOL	
EPCRA 302 EHS TPQ:		
108-95-2	PHENOL (Phenols)	
EPCRA 304 EHS RQ:		
108-95-2 CERCLA RQ:	PHENOL (Phenols)	
CERCLA RQ.		
108-95-2	PHENOL (Phenols)	
141-78-6	ETHYL ACETATE	
108-10-1	4-METHYLPENTAN-2-ONE	
67-56-1	METHANOL	
EPCRA 313 TRI:		
108-95-2	PHENOL (Phenols)	
108-10-1	4-METHYLPENTAN-2-ONE	
67-56-1	METHANOL	
RCRA Code:		

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

108-95-2	PHENOL (Phenols)
141-78-6	ETHYL ACETATE
108-10-1	4-METHYLPENTAN-2-ONE
67-56-1	METHANOL
CAA 112 (r) RMP TQ:	
No component(s) listed.	
State Regulations	
Massachussetts:	
64-17-5	ETHANOL
108-95-2	PHENOL (Phenols)
141-78-6	ETHYL ACETATE
569-61-9	Basic Fuchsin
108-10-1	4-METHYLPENTAN-2-ONE
67-56-1	METHANOL
Minnesota:	
64-17-5	ETHANOL
108-95-2	PHENOL (Phenols)
141-78-6	ETHYL ACETATE
569-61-9	Basic Fuchsin
108-10-1	4-METHYLPENTAN-2-ONE
67-56-1	METHANOL
New Jersey:	
64-17-5	ETHANOL
108-95-2	PHENOL (Phenols)
141-78-6	ETHYL ACETATE
569-61-9	Basic Fuchsin
108-10-1	4-METHYLPENTAN-2-ONE
67-56-1	METHANOL
New York:	
108-95-2	PHENOL (Phenols)
141-78-6	ETHYL ACETATE
108-10-1	4-METHYLPENTAN-2-ONE
67-56-1	METHANOL
Pennsylvania:	
64-17-5	ETHANOL
108-95-2	PHENOL (Phenols)
141-78-6	ETHYL ACETATE
108-10-1	4-METHYLPENTAN-2-ONE

Revision nr. 1 Dated 3/5/2021 First compilation

Printed on 3/5/2021 Page n. 15/18

	Revision nr. 1		
		CAL CORPORATION	Dated 3/5/2021
			First compilation
	C1030 - Carbol-Fu	chsin (Ziehl-Neelsen)	Printed on 3/5/2021
		, ,	Page n. 16/18
67-56-1		METHANOL	
California:			
64-17-5		ETHANOL	
108-95-2		PHENOL (Phenols)	
141-78-6		ETHYL ACETATE	
108-10-1		4-METHYLPENTAN-2-ONE	
67-56-1		METHANOL	
Proposition 65:			
WARNING! This p	roduct contains chemicals known to th	e State of California to cause cancer and birth d	efects or reproductive harm.
569-61-9		Basic Fuchsin C	
108-10-1		4-METHYLPENTAN-2-ONE C/D	
67-56-1		METHANOL D	
International Regu	lations		
Substances subject	ct to exportation reporting pursuant to	(EC) Reg. 649/2012:	
None			
Substances subje	ct to the Rotterdam Convention:		
None			
None			
Substances subje	ct to the Stockholm Convention:		
Nono			
None			
Candadian WHMI	<u>6</u>		
Information not av	ailable		
16. Other in	formation		
	normation		
Text of hazard (H)	indications mentioned in section 2-3 c	of the sheet:	
U225	1 Back to Generate the Part 1		
H225	Highly flammable liquid and	i vapour.	
H350 H351	May cause cancer.	or.	
H341	Suspected of causing canc		
H301	Suspected of causing gene Toxic if swallowed.		
H311	Toxic in swallowed. Toxic in contact with skin.		
1	TONIC IT COMACT WITH SAIL.		

H331 Toxic if inhaled.

H370 Causes damage to organs.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Revision nr. 1 **EXAXOL CHEMICAL CORPORATION** Dated 3/5/2021 First compilation Printed on 3/5/2021 C1030 - Carbol-Fuchsin (Ziehl-Neelsen) Page n. 17/18 H319 Causes serious eye irritation. H335 May cause respiratory irritation. H411 Toxic to aquatic life with long lasting effects. LEGEND: 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code ADR: European Agreement concerning the carriage of Dangerous goods by Road CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®) CAS NUMBER: Chemical Abstract Service Number CE50: Effective concentration (required to induce a 50% effect) CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act) CLP: EC Regulation 1272/2008 DEA: Drug Enforcement Administration EmS: Emergency Schedule EPA: US Environmental Protection Agency EPCRA: Emergency Planning and Community Right-to Know Act EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code) EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code) EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code) GHS: Globally Harmonized System of classification and labeling of chemicals IATA DGR: International Air Transport Association Dangerous Goods Regulation IC50: Immobilization Concentration 50% IMDG: International Maritime Code for dangerous goods IMO: International Maritime Organization LC50: Lethal Concentration 50% LD50: Lethal dose 50% **OEL: Occupational Exposure Level** PEL: Predicted exposure level RCRA Code: Resource Conservation and Recovery Act Code **REL:** Recommended exposure limit RID: Regulation concerning the international transport of dangerous goods by train TLV: Threshold Limit Value TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure. **TSCA:** Toxic Substances Control Act TWA STEL: Short-term exposure limit TWA: Time-weighted average exposure limit VOC: Volatile organic Compounds WHMIS: Workplace Hazardous Materials Information System. GENERAL BIBLIOGRAPHY: - GHS rev. 3 The Merck Index. 10th Edition Handling Chemical Safety Niosh - Registry of Toxic Effects of Chemical Substances INRS - Fiche Toxicologique (toxicological sheet) Patty - Industrial Hygiene and Toxicology N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition ECHA website Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy 6 NYCRR part 597 Cal/OSHA website California Safe Drinking Water and Toxic Enforcement Act EPA website Hazard Comunication Standard (HCS 2012) IARC website List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act Massachussetts 105 CMR Department of public health 670.000: "Right to Know" Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know". New Jersey Worker and Community Right to know Act N.J.S.A. NTP. 2011. Report on Carcinogens, 12th Edition. **OSHA** website Pennsylvania, Hazardous Substance List, Chapter 323 Note for users:

Revision nr. 1

Dated 3/5/2021 First compilation

C1030 - Carbol-Fuchsin (Ziehl-Neelsen)

Printed on 3/5/2021

Page n. 18/18

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.