EXAXOL CHEMI	CAL CORPORATION	Revision nr. 1 Dated 29/1/2016
H3020 - Hardne	ss Buffer, Odorless	Printed on 1/29/2016
	Page n. 1/12	
Safety data sheet ac	cording to U.S.A. Federal	Hazcom 2012
SECTION 1. Identification of the subs	stance/mixture and of the company/un	dertaking
1.1. Product identifier		
Code: Product name	H3020 Hardness Buffer, Odorless	
1.2. Relevant identified uses of the substance or m      Intended use    For Laboratory Use C		
1.3. Details of the supplier of the safety data sheet		
Name	EXAXOL CHEMICAL CORPORATION	
Full address District and Country	14325 60 TH ST N 33760 CLEARWATER - FLORIDA	
	US	
	Tel. 1-727-524-7732	
	Fax 1-727-532-8221	
e-mail address	into Coursel and	
	info@exaxol.com	
<b>1.4. Emergency telephone number</b> For urgent inquiries refer to	1-800-255-3924	
	ChemTel Inc.	
SECTION 2. Hazards identification.		

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement. Flammable liquid, category 4 Acute toxicity, category 4 Skin corrosion, category 1B Serious eye damage, category 1 Specific target organ toxicity - single exposure, category 3

Danger

Combustible liquid. Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. May cause respiratory irritation.

Hazard statements:

Signal words:

# H3020 - Hardness Buffer, Odorless

Revision nr. 1

Dated 29/1/2016

Printed on 1/29/2016 Page n. 2/12

H227	Combustible liquid.		
H302	Harmful if swallowed.		
H314	Causes severe skin burns and eye damage.		
H335	May cause respiratory irritation.		
Precautionary statement	S:		
Prevention:			
P260	Do not breathe dust / fume / gas / mist / vapours / spray.		
P264 P270	Wash skin thoroughly after handling.		
P271	Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.		
P280	Wear protective gloves / protective clothing / eye protection / face protection.		
lesponse:			
P301+P312	IF SWALLOWED: call a POISON CENTER / doctor if you feel unwell.		
P301+P330+P331	IF SWALLOWED: rinse mouth. Do not induce vomiting.		
P303+P361+P353	IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.		
P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.		
P305+P351+P338	IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue		
	rinsing.		
P310	Immediately call a POISON CENTER / doctor.		
P321	Specific treatment (see label).		
P330	Rinse mouth.		
P363	Wash contaminated clothing before reuse.		
Storage:	Chara in a well wantilated place. Know anothing tighthy along d		
P403+P233 P405	Store in a well-ventilated place. Keep container tightly closed.		
	Store locked up.		
0isposal: <b>P501</b>	Dispose of contents / container to an approved waste disposal plant.		
2.2. Other hazards.			
Environmental classifica	tion as for Reg. (EU) 1272/2008 (CLP):		
he product is classified	as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).		
Classification and Hazar			
Hazardous to the aqua	tic environment, chronic toxicity, category 3 Harmful to aquatic life with long lasting effects.		
lazard statements:			
H412	Harmful to aquatic life with long lasting effects.		
recautionary statement	S:		
Prevention:			
P273	Avoid release to the environment.		
Response:	Avoid felease to the environment.		
-			
Storage:			
-			
Disposal:			
P501	Dispose of contents / container to an approved waste disposal plant.		
-			
Additional hazards.			
<b>SECTION 3. Co</b>	mposition/information on ingredients.		
24 Cubatancas			
3.1. Substances.			

# H3020 - Hardness Buffer, Odorless

Revision nr. 1

Dated 29/1/2016

## Printed on 1/29/2016 Page n. 3/12

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification:
WATER		
CAS. 7732-18-5	50 - 100	
Ethanolamine		
CAS. 141-43-5	30 - 50	Flammable liquid, category 4 H227, Acute toxicity, category 4 H302, Acute toxicity, category 4 H312, Acute toxicity, category 4 H332, Skin corrosion, category 1B H314, Specific target organ toxicity - single exposure, category 3 H335, Hazardous to the aquatic environment, chronic toxicity, category 3 H412
Hydrochloric Acid		
CAS. 7647-01-0	1 - 3	Substance or mixture corrosive to metals, category 1 H290, Skin corrosion, category 1B H314, Specific target organ toxicity - single exposure, category 3 H335

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures.**

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention. INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

Revision nr. 1

# H3020 - Hardness Buffer, Odorless

Dated 29/1/2016 Printed on 1/29/2016

Page n. 4/12

## **SECTION 5. Firefighting measures.**

### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6.** Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

		EXAXOL	CHEMICA		RATION		Revision nr. 1 Dated 29/1/2016
H3020 - H			Hardness	ardness Buffer, Odorless			Printed on 1/29/2016 Page n. 5/12
SECTION	7. Handli	ng and sto	orage.				
7.1. Precautic	ons for safe h	andling.					
Ensure that ther or mists. Do not	e is an adequ eat, drink or s	uate earthing s smoke during u	vstem for the eq se. Wash hands	uipment and p after use. Avc	ersonnel. Avoid co id leakage of the p	ntact with eyes and roduct into the envi	l skin. Do not breathe powders, vapours ronment.
7.2. Condition	ns for safe st	orage, includi	ng any incomp	atibilities.			
							containers well sealed. Keep the production to the production of the section 10 for details.
7.3. Specific e	end use(s).						
formation not a	available.						
SECTION	8. Expos	ure contro	ls/persona	I protectio	on.		
8.1. Control p	arameters.						
Regulatory Refe	rences:						
USA USA			Occupati	NIOSH publication No. 2005-149, 3th printing, 20 Occupational Exposure Limits - Limits for Air Cor 1910.1000.			7.
	USA CAL/OSHA-PEL		1910.100	California Division of Occupational Safety and Health Permissible Exposure Limits (PELs).			minants TABLE Z-1-
USA	CAL/USH	A-PEL		a Division of	Occupational S	Safety and Heal	
Ethanolamine	•	A-PEL		a Division of	Occupational S	Safety and Heal	
Ethanolamine	•	A-PEL Country	Permissil	a Division of ole Exposur	Occupational S e Limits (PELs) STEL/15min	Safety and Heal	
Ethanolamine Threshold Lir Type	•	Country	Permissil TWA/8h mg/m3	a Division of ole Exposur ppm	Occupational S e Limits (PELs)	Safety and Heal	
Ethanolamine Threshold Lir Type OSHA	•	Country USA	Permissil TWA/8h mg/m3 6	a Division of ole Exposur ppm 3	Occupational S e Limits (PELs) STEL/15min mg/m3	Safety and Heal ppm	
Ethanolamine Threshold Lir	•	Country	Permissil TWA/8h mg/m3	a Division of ole Exposur ppm	Occupational S e Limits (PELs) STEL/15min	Safety and Heal	
Ethanolamine Threshold Lin Type OSHA CAL/OSHA NIOSH Hydrochloric	e nit Value. Acid	Country USA USA	Permissil TWA/8h mg/m3 6 8	ppm 3 3	Occupational S e Limits (PELs) STEL/15min mg/m3 15	Safety and Heal ppm 6	
Ethanolamine Threshold Lin Type OSHA CAL/OSHA NIOSH	e nit Value. Acid	Country USA USA	Permissil TWA/8h mg/m3 6 8 8 8	ppm 3 3 3	Occupational S e Limits (PELs) STEL/15min mg/m3 15 15 15 STEL/15min	Safety and Heal ppm 6 6	
Ethanolamine Threshold Lin Type OSHA CAL/OSHA NIOSH Hydrochloric Threshold Lin Type	e nit Value. Acid	Country USA USA USA Country	Permissil TWA/8h mg/m3 6 8 8	ppm 3 3	Occupational S e Limits (PELs) STEL/15min mg/m3 15 15 STEL/15min mg/m3	Safety and Heal ppm 6 6 9	
Ethanolamine Threshold Lin Type OSHA CAL/OSHA NIOSH Hydrochloric Threshold Lin Type OSHA	e nit Value. Acid	Country USA USA USA Country USA	Permissil TWA/8h mg/m3 6 8 8 TWA/8h mg/m3	ppm 3 3 3	Occupational S e Limits (PELs) STEL/15min mg/m3 15 15 15 STEL/15min	Safety and Heal ppm 6 6	
Ethanolamine Threshold Lin Type OSHA CAL/OSHA NIOSH Hydrochloric Threshold Lin Type	e nit Value. Acid	Country USA USA USA Country	Permissil TWA/8h mg/m3 6 8 8 8	ppm 3 3 3	Occupational S e Limits (PELs) STEL/15min mg/m3 15 15 STEL/15min mg/m3	Safety and Heal ppm 6 6 9	

## 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired

Revision nr. 1

# H3020 - Hardness Buffer, Odorless

Printed on 1/29/2016 Page n. 6/12

Dated 29/1/2016

## through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must comply with current regulations.

Provide an emergency shower with face and eye wash station.

## HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

## SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

## EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

°C.

# **SECTION 9.** Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	Not available.
Colour	Not available.
Odour	Not available.
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	60 < T ≤ 93
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.

## H3020 - Hardness Buffer, Odorless

Revision nr. 1

Dated 29/1/2016 Printed on 1/29/2016

Page n. 7/12

Vapour density Relative density. Solubility Partition coefficient: n-octanol/water Auto-ignition temperature. Decomposition temperature. Viscosity Explosive properties Oxidising properties Not available. 1.007 Kg/l Not available. Not available. Not available. Not available. Not available. Not available. Not available.

### 9.2. Other information.

Information not available.

## **SECTION 10. Stability and reactivity.**

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials.

Information not available.

#### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

# **SECTION 11. Toxicological information.**

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

EXAXOL CHEMICAL CORPORATION	Revision nr. 1
	Dated 29/1/2016
H3020 - Hardness Buffer, Odorless	Printed on 1/29/2016 Page n. 8/12

Acute effects: ingestion of this product is harmful. Even small amounts of product may cause serious health problems (stomach pain, nausea, sickness, diarrhoea).

This product is corrosive and causes serious burns and vesicles on the skin, which can arise even after exposure. Burns are very stinging and painful. Upon contact with eyes, it may cause serious harm, such as cornea opacity, iris lesions, irreversible eye coloration. The vapors and/or powders are caustic for the respiratory system and may cause pulmonary edema, whose symptoms sometimes arise only after some hours.

Exposure symptoms may include: sting, cough, asthma, laryngitis, respiratory disorders, headache, nausea and sickness.

If swallowed, it may cause mouth, throat and oesophagus burns, sickness, diarrhoea, edema, larynx swelling and, consequently, asphyxia. Perforation of the gastro-intestinal tract is also possible.

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

Acute effects: inhalation of this product may irritate the lower and upper respiratory tract and cause cough and respiratory disorders; at higher concentrations it can also cause pulmonary edema. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Carcinogenicity Assessment:7647-01-0Hydrochloric Acid IARC:3

## **SECTION 12. Ecological information.**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment. **12.1. Toxicity.** Information not available.

## 12.2. Persistence and degradability.

Information not available.

### 12.3. Bioaccumulative potential.

Information not available.

### 12.4. Mobility in soil.

Information not available.

#### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

## **SECTION 13. Disposal considerations.**

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

### Revision nr. 1 Dated 29/1/2016

# H3020 - Hardness Buffer, Odorless

Printed on 1/29/2016

Page n. 9/12

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information.**

## **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

U.S. Federal Regulations.

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

7647-01-0

Hydrochloric Acid

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

<u>Clean Water Act –</u> Priority Pollutants:

No component(s) listed.

<u>Clean Water Act –</u> <u>Toxic Pollutants:</u>

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

EPA List of Lists:

313 Category Code:

7647-01-0 7647-01-0 EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

Hydrochloric Acid Hydrochloric Acid

EXAMOL CHEMICAL CORPORATION	Revision nr. 1 Dated 29/1/2016
H3020 - Hardness Buffer, Odorless	Printed on 1/29/2016 Page n. 10/12

No component(s) listed.		
CERCLA RQ:		
7647-01-0	Hydrochloric Acid	
EPCRA 313 TRI:		
7647-01-0	Hydrochloric Acid	
RCRA Code:		
No component(s) listed.		
CAA 112 (r) RMP TQ:		
7647-01-0	Hydrochloric Acid	
State Regulations.		
Massachussetts:		
141-43-5	Ethanolamine	
7647-01-0	Hydrochloric Acid	
<u>Minnesota:</u>		
141-43-5	Ethanolamine	
7647-01-0	Hydrochloric Acid	
<u>New Jersey:</u>		
141-43-5	Ethanolamine	
7647-01-0	Hydrochloric Acid	
New York:		
7647-01-0	Hydrochloric Acid	
Pennsylvania:		
141-43-5	Ethanolamine	
7647-01-0	Hydrochloric Acid	
<u>California:</u>		
141-43-5	Ethanolamine	
7647-01-0	Hydrochloric Acid	
Proposition 65:		
International Regulations.		
Substances subject to exportation reporting	pursuant to (EC) Reg. 649/2012:	
None.		
Substances subject to the Rotterdam Conve	antion:	
None		

None.

EXAXOL CHEMICAL CO	ORPORATION
--------------------	------------

Revision nr. 1

# H3020 - Hardness Buffer, Odorless

Dated 29/1/2016

Printed on 1/29/2016 Page n. 11/12

Substances subject to the Stockholm Convention:

None.

Candadian WHMIS.

Information not available.

## **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 4	Flammable liquid, category 4
Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic toxicity, category 4
H227	Combustible liquid.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
  GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation

Revision nr. 1

# H3020 - Hardness Buffer, Odorless

Dated 29/1/2016

Printed on 1/29/2016 Page n. 12/12

Provide appointed staff with adequate training on how to use chemical products.