

Safety data sheet according to U.S.A. Federal Hazcom 2012

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: L4920
Product name: Lead Acetate 10% w/v RS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: For Laboratory Use Only

1.3. Details of the supplier of the safety data sheet

Name: EXAXOL CHEMICAL CORPORATION
Full address: 14325 60 TH ST N
District and Country: 33760 CLEARWATER - FLORIDA
US
Tel. 1-727-524-7732
Fax 1-727-532-8221

e-mail address

info@exaxol.com

1.4. Emergency telephone number

For urgent inquiries refer to: 1-800-255-3924
ChemTel Inc.

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement.

Reproductive toxicity, category 1A
Eye irritation, category 2
Skin irritation, category 2

May damage fertility or the unborn child.
Causes serious eye irritation.
Causes skin irritation.



Signal words:

Danger

Hazard statements:

H360: May damage fertility or the unborn child.
H319: Causes serious eye irritation.

H315 Causes skin irritation.

Precautionary statements:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

Response:

P302+P352 IF ON SKIN: wash with plenty of water.
P305+P351+P338 IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: get medical advice.
P321 Specific treatment (see label).
P332+P313 If skin irritation occurs: get medical advice.
P337+P313 If eye irritation persists: get medical advice / attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents / container to an approved waste disposal plant.

2.2. Other hazards.

Environmental classification as for Reg. (EU) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement.

Hazardous to the aquatic environment, chronic toxicity, category 2

Toxic to aquatic life with long lasting effects.



Hazard statements:

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

Prevention:

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

--

Storage:

--

Disposal:

P501 Dispose of contents / container to an approved waste disposal plant.

--

Additional hazards.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification:
WATER		
CAS. 7732-18-5	50 - 100	
Lead Acetate Trihydrate		
CAS. 6080-56-4	9 - 25	Reproductive toxicity, category 1A H360, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1, Hazardous to the aquatic environment, chronic toxicity, category 1 H410
ACETIC ACID		
CAS. 64-19-7	1 - 3	Flammable liquid, category 3 H226, Skin corrosion, category 1A H314

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.**SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.**6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

L4920 - Lead Acetate 10% w/v RS

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.**8.1. Control parameters.**

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC;
	TLV-ACGIH	Directive 2000/39/EC. ACGIH 2014

ACETIC ACID**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
OEL	EU	25	10		
TLV-ACGIH	-	25	10	37	15
OSHA	USA	25	10		
CAL/OSHA	USA	25	10	37 (C)	40 (C)
NIOSH	USA	25	10	37	15

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must comply with current regulations.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	Not available.
Colour	Not available.
Odour	Not available.
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	> 93 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1.068 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

ACETIC ACID: risk of explosion on contact with: chromium (IV) oxide, potassium permanganate, sodium peroxide, perchloric acid, phosphorus chloride, hydrogen peroxide. Can react dangerously with: alcohols, bromine pentafluoride, chlorosulphuric acid, dichromate-sulphuric acid, ethane diamine, ethylene glycol, potassium hydroxide, strong bases, sodium hydroxide, strong oxidising agent, nitric acid, ammonium nitrate, potassium tert-butoxide, oleum. Forms explosive mixtures with air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ACETIC ACID: avoid exposure to sources of heat and naked flames.

10.5. Incompatible materials.

ACETIC ACID: carbonates, hydroxides, many oxides and phosphates. Oxidising substances and bases.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product has a teratogenic effect on human beings: damages fertility and/or has toxic effects on fetus development.

There is sufficient evidence to make us believe that the substance contained in the product is likely to affect the embryo-fetal development and/or the fetus development.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin.

Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

ACETIC ACID

LD50 (Oral).3310 mg/kg Rat

LD50 (Dermal).1060 mg/kg Rabbit

LC50 (Inhalation).11.4 mg/l/4h Rat

SECTION 12. Ecological information.

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.**ACETIC ACID**

Solubility in water.

> 10000 mg/l

Rapidly biodegradable.

12.3. Bioaccumulative potential.**ACETIC ACID**

Partition coefficient: n-octanol/water.

-0.17

12.4. Mobility in soil.**ACETIC ACID**

Partition coefficient: soil/water.

1.153

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.**13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to dangerous goods transport regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG,
IATA:

UN: 3082

14.2. UN proper shipping name.

ADR / RID: ENVIRONMENT
ALLY
HAZARDOUS
SUBSTANCE,
LIQUID, N.O.S.
(Lead Acetate
Trihydrate)
IMDG: ENVIRONMENT
ALLY
HAZARDOUS
SUBSTANCE,
LIQUID, N.O.S.
(Lead Acetate
Trihydrate)
IATA:

14.3. Transport hazard class(es).

ADR / RID: Class: 9 Label: 9
IMDG: Class: 9 Label: 9
IATA: Class: 9 Label: 9



14.4. Packing group.

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards.

ADR / RID: Environmentally
Hazardous.
IMDG: Marine Pollutant.
IATA: Environmentally
Hazardous.



14.6. Special precautions for user.

EXAXOL CHEMICAL CORPORATION

Revision nr. 2

Dated 8/6/2016

L4920 - Lead Acetate 10% w/v RS

Printed on 6/8/2016

Page n. 10/14

ADR / RID:	Nr. Kemler: 90	Limited Quantity 5 L	Tunnel restriction code (E)
IMDG:	Special Provision: - EMS: F-A, S-F	Limited Quantity 5 L	
IATA:	Cargo:	Maximum quantity: 450 L	Packaging instructions: 964
	Pass.:	Maximum quantity: 450 L	Packaging instructions: 964
	Special Instructions:	A97, A158, A197	

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**U.S. Federal Regulations.Clean Air Act Section 112(b):

6080-56-4

Lead Acetate Trihydrate (Lead
compounds)Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act –
Priority Pollutants:

No component(s) listed.

Clean Water Act –
Toxic Pollutants:

6080-56-4

Lead Acetate Trihydrate (Lead
compounds)DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EXAXOL CHEMICAL CORPORATION

Revision nr. 2

Dated 8/6/2016

L4920 - Lead Acetate 10% w/v RS

Printed on 6/8/2016

Page n. 11/14

EPA List of Lists:

313 Category Code:

6080-56-4

Lead Acetate Trihydrate (Lead compounds)

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

64-19-7

ACETIC ACID

EPCRA 313 TRI:

6080-56-4

Lead Acetate Trihydrate (Lead compounds)

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations.Massachusetts:

64-19-7

ACETIC ACID

Minnesota:

64-19-7

ACETIC ACID

New Jersey:

6080-56-4

Lead Acetate Trihydrate (Lead compounds)

64-19-7

ACETIC ACID

New York:

64-19-7

ACETIC ACID

Pennsylvania:

6080-56-4

Lead Acetate Trihydrate (Lead compounds)

64-19-7

ACETIC ACID

California:

6080-56-4

Lead Acetate Trihydrate (Lead compounds)

64-19-7

ACETIC ACID

Proposition 65:

WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

6080-56-4

Lead Acetate Trihydrate (Lead compounds)

International Regulations.Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Canadian WHMIS.

Information not available.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Repr. 1A	Reproductive toxicity, category 1A
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic toxicity, category 4
H226	Flammable liquid and vapour.
H360	May damage fertility or the unborn child.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

EXAXOL CHEMICAL CORPORATION

Revision nr. 2

Dated 8/6/2016

L4920 - Lead Acetate 10% w/v RS

Printed on 6/8/2016

Page n. 13/14

- H412** Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 05 / 07 / 08 / 09 / 10 / 11 / 12 / 15 / 16.