EXAXOL CH	IEMICAL CORPORATION	Revision nr. 2
	Dated 11/3/2022	
MS3 - Multi-ele	Printed on 11/3/2022	
		Page n. 1/14
		Replaced revision:1 (Dated: 11/3/2022)
	Safety Data Sheet According to U.S.A. Federal Hazcom 2012	
1. Identification		
1.1. Product identifier		
Code:	MS3 Multi-element 3 in 10% HCI/ 1% HNO3	
Product name	Multi-element 3 in 10% HCl/ 1% HNO3	
1.2. Relevant identified uses of the substan Intended use For Laborator		
1.3. Details of the supplier of the safety dat		
Name Full address District and Country	EXAXOL CHEMICAL CORPORATION 14325 60 TH ST N 33760 CLEARWATER - FLORIDA US	
	Tel. 1-727-524-7732	
	Fax 1-727-532-8221	
e-mail address		
	info@exaxol.com	
1.4. Emergency telephone number For urgent inquiries refer to	1-800-255-3924 ChemTel Inc.	
2. Hazards identification		
1. Classification of the substance or mixtur	e	
ne product is classified as hazardous pursuan	t to the provisions set forth in OSHA Hazard Communicat	ion Standard (HCS) (29 CFR 1910 1200) Th
oduct thus requires a safety datasheet.	for health and/or the environment are given in sections 11 a	
assification and Hazard Statement		

Classification and Hazard Statement

Hazard pictograms: Skin corrosion, category 1

Serious eye damage, category 1



Causes severe skin burns and eye damage. Causes serious eye damage.

			Revision nr. 2
		AL CORPORATION	Dated 11/3/2022
	MG2 Multi alamant (3 in 10% HCI/ 1% HNO3	Printed on 11/3/2022
•			Page n. 2/14
			Replaced revision:1 (Dated: 11/3/2022)
Signal words:	Danger		
Hazard statements:			
H314	Causes severe skin burns a	nd eye damage.	
Precautionary statement	s:		
Prevention:			
P260 P280	Do not breathe dust / fume /	gas / mist / vapours / spray. ective clothing / eye protection / face protection.	
P264	Wash skin thoroughly after h		
Response:		-	
P305+P351+P338	IF IN EYES: Rinse cautiousl rinsing.	y with water for several minutes. Remove contact	lenses, if present and easy to do. Continue
P301+P330+P331	IF SWALLOWED: Rinse mo	uth. Do NOT induce vomiting.	
P303+P361+P353		off immediately all contaminated clothing. Rinse sk	in with water / shower.
P310 P304+P340	Immediately call a POISON	UENTER / doctor. It to fresh air and keep comfortable for breathing.	
P363	Wash contaminated clothing		
Storage:			
P405 Disposal:	Store locked up.		
P501	Dispose of contents / contain	ner to an approved waste disposal plant.	
2.2. Other hazards			
Information not available			
3. Composition	/information on ingred	ients	
3.2. Mixtures			
Contains:			
Identification	x = Conc. %	Classification:	
WATER			
CAS 7732-18-5	87 ≤ x < 89		
EC 231-791-2			
INDEX -			
Hydrochloric Acid			
CAS 7647-01-0	10 ≤ x < 11	Substance or mixture corrosive to metals, cate category 1B H314, Serious eye damage, cate	gory 1 H318, Specific target
EC 231-595-7		organ toxicity - single exposure, category 3 H	335
INDEX -			
NITRIC ACID			
CAS 7697-37-2	1 ≤ x < 1,5	Oxidising liquid, category 2 H272, Skin corros eye damage, category 1 H318	ion, category 1A H314, Serious
FC 004 744 0		cyc damaye, calegory Thoro	

EC 231-714-2 INDEX 007-004-00-1

MS3 - Multi-element 3 in 10% HCl/ 1% HNO3

Revision nr. 2

Dated 11/3/2022 Printed on 11/3/2022

Page n. 3/14

Replaced revision:1 (Dated: 11/3/2022)

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Revision nr. 2

Dated 11/3/2022

Printed on 11/3/2022 Page n. 4/14

Replaced revision:1 (Dated: 11/3/2022)

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

	USA USA USA EU	NIOSH-REL OSHA-PEL CAL/OSHA-PEL OEL EU TLV-ACGIH	NIOSH publication No. 2005-149, 3th printing, 2007. Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000. California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs). Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC. ACGIH 2018
--	-------------------------	--	--

Country	TWA/8h		STEL/15min		
	mg/m3	ppm	mg/m3	ppm	
USA			7 (C)	5 (C)	
USA	7	5			
USA			7 (C)	5 (C)	
-	USA	mg/m3 USA USA 7	mg/m3 ppm USA 7 5	mg/m3 ppm mg/m3 USA 7 (C) USA 7 5	mg/m3 ppm mg/m3 ppm USA 7 (C) 5 (C) USA 7 5

MS3 - Multi-element 3 in 10% HCl/ 1% HNO3

Revision nr. 2

Dated 11/3/2022

Printed on 11/3/2022 Page n. 5/14

Replaced revision:1 (Dated: 11/3/2022)

NITRIC ACID

9						
Country	TWA/8h	TWA/8h		STEL/15min		
	mg/m3	ppm	mg/m3	ppm		
-	5.2	2	10.3	4		
EU			2.6	1		
USA	5	2				
USA	5	2	10	4		
USA	5	2	10	4		
	Country - EU USA USA	CountryTWA/8hmg/m3-5.2EUUSA5USA5	CountryTWA/8hmg/m3ppm-5.22EUUSA52USA52USA52	Country TWA/8h STEL/15min mg/m3 ppm mg/m3 - 5.2 2 10.3 EU 2.6 USA 5 2 USA 5 2 10	Country TWA/8h STEL/15min mg/m3 ppm mg/m3 ppm - 5.2 2 10.3 4 EU 2.6 1 USA 5 2 10 4	Country TWA/8h STEL/15min mg/m3 ppm mg/m3 ppm - 5.2 2 10.3 4 EU 2.6 1 1 USA 5 2 10 4

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	Not available
Odour	Not available
Odour threshold	Not available

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Not available Not available Not available Not available > 93 °C Not available Revision nr. 2

Dated 11/3/2022

Printed on 11/3/2022 Page n. 6/14

Replaced revision:1 (Dated: 11/3/2022)

pH Melting point / freezing point Initial boiling point Boiling range Flash point Evaporation Rate Flammability of solids and gases Lower inflammability limit Upper inflammability limit Lower explosive limit Upper explosive limit Upper explosive limit Vapour pressure Vapour density Relative density Solubility Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature Viscosity Explosive properties

9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

Hydrochloric Acid

Corrodes: metals.

NITRIC ACID

Decomposes at 84°C/183°F.Possibility of self-ignition.

10.2. Chemical stability

Hydrochloric Acid

Stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The product may react violently with water.

Hydrochloric Acid

Develops heat on contact with: amines,aldehydes,permanganates.May form pyrophoric mixtures with: aluminium,fluorine,metals,bases,sulphur compounds.Risk of explosion on contact with: sulphuric acid,alkaline metals.

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Revision nr. 2

Dated 11/3/2022 Printed on 11/3/2022

Page n. 7/14

Replaced revision:1 (Dated: 11/3/2022)

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

NITRIC ACID

Avoid exposure to: heat, light.

10.5. Incompatible materials

Hydrochloric Acid

Incompatible materials: metals.

NITRIC ACID

Incompatible with: flammable substances, reducing substances, alcohol, metals, basic substances, acetone, acetic acid, acetic anhydride. Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

NITRIC ACID

May develop: nitric oxide.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Revision nr. 2

Dated 11/3/2022

Printed on 11/3/2022 Page n. 8/14

Replaced revision:1 (Dated: 11/3/2022)

Information not available

ACUTE TOXICITY

Corrosive to the respiratory tract.

NITRIC ACID

LC50 (Inhalation) 67 ppm/4h Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment: 7647-01-0Hydrochloric Acid IARC:3

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Revision nr. 2

Dated 11/3/2022

Printed on 11/3/2022 Page n. 9/14

Replaced revision:1 (Dated: 11/3/2022)

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Hydrochloric Acid LC50 - for Fish

282 mg/l/96h Gambusia affinis (mosquito fish)

12.2. Persistence and degradability

NITRIC ACID Solubility in water Degradability: information not available

> 100000 mg/l

< 3

12.3. Bioaccumulative potential

NITRIC ACID
Partition coefficient: n-octanol/water

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, 3264 IATA:

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Revision nr. 2

Dated 11/3/2022

Printed on 11/3/2022 Page n. 10/14

Replaced revision:1 (Dated: 11/3/2022)

14.2. UN proper shipping name

ADR / RID:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrochloric Acid; NITRIC ACID)
IMDG:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrochloric Acid; NITRIC ACID)
IATA:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hydrochloric Acid; NITRIC ACID)

14.3. Transport hazard class(es)

ADR / RID:	Class: 8	Label: 8	
IMDG:	Class: 8	Label: 8	
IATA:	Class: 8	Label: 8	8



14.4. Packing group

ADR / RID, IMDG, II IATA:

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 80 Special Provision: -	Limited Quantities: 1 L	Tunnel restriction code: (E)
IMDG:	EMS: F-A, S-B	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 30 L	Packaging instructions: 855
	Pass.:	Maximum quantity: 1 L	Packaging instructions: 851
	Special Instructions:	A3, A803	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Revision nr. 2

Dated 11/3/2022

Printed on 11/3/2022 Page n. 11/14

Replaced revision:1 (Dated: 11/3/2022)

tion specific for the substance or mixture
Hydrochloric Acid
Hydrochloric Acid
Hydrochloric Acid
NITRIC ACID
Antimony(III) Oxide (Antimony compounds)
compounds)
NITRIC ACID
NITRIC ACID

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Revision nr. 2

Dated 11/3/2022

Printed on 11/3/2022 Page n. 12/14

Replaced revision:1 (Dated: 11/3/2022)

		Replaced revision: 1 (Dated: 11/3/2022)
7647-01-0	Hydrochloric Acid	
7697-37-2	NITRIC ACID	
1309-64-4	Antimony(III) Oxide (Antimony	
EPCRA 313 TRI:	compounds)	
7647-01-0	Hydrochloric Acid	
7697-37-2	NITRIC ACID	
1309-64-4	Antimony(III) Oxide (Antimony compounds)	
RCRA Code:		
No component(s) listed.		
CAA 112 (r) RMP TQ:		
7647-01-0	Hydrochloric Acid	
State Regulations		
Massachussetts:		
7647-01-0	Hydrochloric Acid	
7697-37-2	NITRIC ACID	
Minnesota:		
7647-01-0	Hydrochloric Acid	
7697-37-2	NITRIC ACID	
New Jersey:		
7647-01-0	Hydrochloric Acid	
7697-37-2	NITRIC ACID	
New York:		
7647-01-0	Hydrochloric Acid	
7697-37-2	NITRIC ACID	
Pennsylvania:		
7047.04.0		
7647-01-0 7697-37-2	Hydrochloric Acid NITRIC ACID	
California:	NITRIC ACID	
Canoma.		
7647-01-0	Hydrochloric Acid	
7697-37-2	NITRIC ACID	
Proposition 65:		
International Regulations		
Substances subject to exportation reporting	pursuant to (EC) Reg. 649/2012:	
None		

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Revision nr. 2

Dated 11/3/2022 Printed on 11/3/2022

Page n. 13/14

Replaced revision:1 (Dated: 11/3/2022)

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Candadian WHMIS

Information not available

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H272May intensify fire; oxidiser.H290May be corrosive to metals.H314Causes severe skin burns and eye damage.H318Causes serious eye damage.H335May cause respiratory irritation.		
H314Causes severe skin burns and eye damage.H318Causes serious eye damage.	H272	May intensify fire; oxidiser.
H318Causes serious eye damage.	H290	May be corrosive to metals.
	H314	Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.	H318	Causes serious eye damage.
	H335	May cause respiratory irritation.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

MS3 - Multi-element 3 in 10% HCI/ 1% HNO3

Revision nr. 2

Dated 11/3/2022

Printed on 11/3/2022 Page n. 14/14

Replaced revision:1 (Dated: 11/3/2022)

GENERAL BIBLIOGRAPHY:

- GHS rev. 3

- The Merck Index. 10th Edition

Handling Chemical Safety

- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act

- EPA website

- Hazard Comunication Standard (HCS 2012)

- IARC website

- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act

- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323 Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

09.