

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid**Safety data sheet according to U.S.A. Federal Hazcom 2012****SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Code: MS68A
Product name: 68 Element Standard Part A 49 Elements in 2% Nitric Acid

1.2. Relevant identified uses of the substance or mixture and uses advised against
Intended use For Laboratory Use Only.**1.3. Details of the supplier of the safety data sheet**

Name EXAXOL CHEMICAL CORPORATION
Full address 14325 60 TH ST N
District and Country 33760 CLEARWATER - FLORIDA
US
Tel. 1-727-524-7732
Fax 1-727-532-8221

e-mail address

info@exaxol.com

1.4. Emergency telephone number

For urgent inquiries refer to 1-800-255-3924
ChemTel Inc.

SECTION 2. Hazards identification.**2.1. Classification of the substance or mixture.**

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement.

Eye irritation, category 2
Skin irritation, category 2

Causes serious eye irritation.
Causes skin irritation.



Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.
H315 Causes skin irritation.

Precautionary statements:

Prevention:

P264

Wash skin thoroughly after handling.

P280

Wear protective gloves / eye protection / face protection.

Response:

P302+P352

IF ON SKIN: wash with plenty of water.

P305+P351+P338

IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321

Specific treatment (see label).

P332+P313

If skin irritation occurs: get medical advice.

P337+P313

If eye irritation persists: get medical advice / attention.

P362+P364

Take off contaminated clothing and wash it before reuse.

Storage:

--

Disposal:

--

2.2. Other hazards.

The product is not classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.

Conc. %.

Classification:

WATER

CAS. 7732-18-5

50 - 100

NITRIC ACID

CAS. 7697-37-2

1 - 3

Oxidising liquid, category 3
H272, Skin corrosion,
category 1A H314

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid**4.2. Most important symptoms and effects, both acute and delayed.**

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.**5.1. Extinguishing media.****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

5.3. Advice for firefighters.**GENERAL INFORMATION**

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.**6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid**6.3. Methods and material for containment and cleaning up.**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.**7.1. Precautions for safe handling.**

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.**8.1. Control parameters.**

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.	
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.	
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).	
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.	
	TLV-ACGIH	ACGIH 2014	

NITRIC ACID**Threshold Limit Value.**

Type	Country	TWA/8h	STEL/15min
		mg/m3	mg/m3
		ppm	ppm

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid

TLV-ACGIH	-	5.2	2	10.3	4
OEL	EU			2.6	1
OSHA	USA	5	2		
CAL/OSHA	USA	5	2	10	4
NIOSH	USA	5	2	10	4

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must comply with current regulations.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.**9.1. Information on basic physical and chemical properties.**

Appearance	Not available.
Colour	Not available.
Odour	Not available.
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	> 93 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid

Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	Not available.
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.**10.1. Reactivity.**

NITRIC ACID: decomposes at 84°C with possibility of self-ignition.

10.2. Chemical stability.

Information not available.

10.3. Possibility of hazardous reactions.

The product may react violently with water.

10.4. Conditions to avoid.

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

NITRIC ACID: exposure to heat and light.

10.5. Incompatible materials.

NITRIC ACID: flammable substances, reducing substances, alcohol, basic substances and metals; acetone, acetic acid, acetic anhydride and certain plastics.

10.6. Hazardous decomposition products.

NITRIC ACID: nitric oxides.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin.

Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

NITRIC ACID

LC50 (Inhalation).67 ppm/4h Rat

Carcinogenicity Assessment:1314-62-1Vanadium(V) Oxide

IARC:2B

7440-38-2Arsenic

IARC:1

NTP: Known

7440-43-9Cadmium

IARC:1

NTP: Known

7440-41-7Beryllium

IARC:1

NTP: Known

7439-92-1Lead

IARC:2B

NTP: Reasonably Anticipated

7782-49-2Selenium

IARC:3

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.**NITRIC ACID**

Solubility in water. > 1000000 mg/l

Biodegradability: Information not available.

12.3. Bioaccumulative potential.**NITRIC ACID**

Partition coefficient: n-octanol/water. < 3

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid**12.4. Mobility in soil.**

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.**13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to dangerous goods transport regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.**14.1. UN number.**

ADR / RID, IMDG,
IATA:

UN: 3264

14.2. UN proper shipping name.

ADR / RID: CORROSIVE
LIQUID, ACIDIC,
INORGANIC,
N.O.S. (NITRIC
ACID)
IMDG: CORROSIVE
LIQUID, ACIDIC,
INORGANIC,
N.O.S. (NITRIC
ACID)
IATA:

14.3. Transport hazard class(es).

ADR / RID:	Class: 8	Label: 8
IMDG:	Class: 8	Label: 8
IATA:	Class: 8	Label: 8



EXAXOL CHEMICAL CORPORATION

Revision nr. 1

Dated 27/8/2015

Printed on 8/27/2015

Page n. 9/15

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid**14.4. Packing group.**ADR / RID, IMDG, III
IATA:**14.5. Environmental hazards.**

ADR / RID: NO

14.6. Special precautions for user.

ADR / RID:	Nr. Kemler: 80	Limited Quantity 5 L	Tunnel restriction code (E)
IMDG:	Special Provision: - EMS: F-A, S-B	Limited Quantity 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 856
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 852
	Special Instructions:	A3, A803	

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**U.S. Federal Regulations.Clean Air Act Section 112(b):

7440-38-2	Arsenic
7440-48-4	Cobalt Powder
7440-43-9	Cadmium
7440-41-7	Beryllium
7439-92-1	Lead
7782-49-2	Selenium

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

EXAXOL CHEMICAL CORPORATION

Revision nr. 1

Dated 27/8/2015

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid

Printed on 8/27/2015

Page n. 10/15

Clean Water Act –
Priority Pollutants:

7440-38-2	Arsenic
7440-50-8	Copper
7440-43-9	Cadmium
7440-41-7	Beryllium
7439-92-1	Lead
7782-49-2	Selenium
7440-28-0	Thallium

Clean Water Act –
Toxic Pollutants:

7440-38-2	Arsenic
7440-50-8	Copper
7440-43-9	Cadmium
7440-41-7	Beryllium
7439-92-1	Lead
7782-49-2	Selenium
7440-28-0	Thallium

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

7440-38-2	Arsenic
7440-48-4	Cobalt Powder
7440-50-8	Copper
7440-43-9	Cadmium
7440-41-7	Beryllium
7439-92-1	Lead
7761-88-8	Silver Nitrate
7440-28-0	Thallium
1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID

EPCRA 302 EHS TPQ:

1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID

EPCRA 304 EHS RQ:

1314-62-1	Vanadium(V) Oxide
-----------	-------------------

EXAXOL CHEMICAL CORPORATION

Revision nr. 1

Dated 27/8/2015

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid

Printed on 8/27/2015

Page n. 11/15

7697-37-2 NITRIC ACID

CERCLA RQ:

7440-38-2	Arsenic
7440-50-8	Copper
7440-43-9	Cadmium
7440-41-7	Beryllium
7439-92-1	Lead
7761-88-8	Silver Nitrate
7440-28-0	Thallium
1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID

EPCRA 313 TRI:

7440-38-2	Arsenic
7440-48-4	Cobalt Powder
7440-50-8	Copper
7440-43-9	Cadmium
7440-41-7	Beryllium
7439-92-1	Lead
7761-88-8	Silver Nitrate
7440-28-0	Thallium
1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID

RCRA Code:

7440-41-7	Beryllium
1314-62-1	Vanadium(V) Oxide

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations.Massachusetts:

7440-38-2	Arsenic
10022-31-8	Barium Nitrate
7440-48-4	Cobalt Powder
7440-50-8	Copper
7440-43-9	Cadmium
7440-74-6	Indium shot
7440-41-7	Beryllium
7439-92-1	Lead
7757-79-1	Potassium Nitrate
7761-88-8	Silver Nitrate
7631-99-4	Sodium Nitrate
10042-76-9	Strontium Nitrate

EXAXOL CHEMICAL CORPORATION

Revision nr. 1

Dated 27/8/2015

Printed on 8/27/2015

Page n. 12/15

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid

7782-49-2	Selenium
7440-28-0	Thallium
13823-29-5	Thorium Nitrate
1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID

Minnesota:

7440-38-2	Arsenic
7440-48-4	Cobalt Powder
7440-50-8	Copper
7440-43-9	Cadmium
7440-74-6	Indium shot
7439-92-1	Lead
7782-49-2	Selenium
7440-28-0	Thallium
1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID

New Jersey:

7440-38-2	Arsenic
10022-31-8	Barium Nitrate
7440-48-4	Cobalt Powder
7440-50-8	Copper
7440-43-9	Cadmium
7440-74-6	Indium shot
7790-69-4	Lithium Nitrate
7440-41-7	Beryllium
7439-92-1	Lead
13478-00-7	Nickel(II) Nitrate Hexahydrate
7757-79-1	Potassium Nitrate
7761-88-8	Silver Nitrate
10042-76-9	Strontium Nitrate
7782-49-2	Selenium
7440-28-0	Thallium
13823-29-5	Thorium Nitrate
13520-83-7	Uranyl Nitrate
1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID
7440-42-8	BORON

New York:

7440-38-2	Arsenic
7440-50-8	Copper
7440-43-9	Cadmium
7440-41-7	Beryllium
7439-92-1	Lead

EXAXOL CHEMICAL CORPORATION

Revision nr. 1

Dated 27/8/2015

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid

Printed on 8/27/2015

Page n. 13/15

7761-88-8	Silver Nitrate
7782-49-2	Selenium
7440-28-0	Thallium
1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID

Pennsylvania:

7440-38-2	Arsenic
10022-31-8	Barium Nitrate
7440-48-4	Cobalt Powder
7440-50-8	Copper
7440-43-9	Cadmium
7440-74-6	Indium shot
7440-41-7	Beryllium
7439-92-1	Lead
7757-79-1	Potassium Nitrate
7761-88-8	Silver Nitrate
7631-99-4	Sodium Nitrate
10042-76-9	Strontium Nitrate
7782-49-2	Selenium
7440-28-0	Thallium
13823-29-5	Thorium Nitrate
1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID

California:

7440-38-2	Arsenic
7440-48-4	Cobalt Powder
7440-50-8	Copper
7440-43-9	Cadmium
7440-74-6	Indium shot
7440-41-7	Beryllium
7439-92-1	Lead
7761-88-8	Silver Nitrate
7440-28-0	Thallium
1314-62-1	Vanadium(V) Oxide
7697-37-2	NITRIC ACID

Proposition 65:

WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

7440-48-4	Cobalt Powder C
7440-43-9	Cadmium C/D/R
7440-41-7	Beryllium C
7439-92-1	Lead C/D/R
1314-62-1	Vanadium(V) Oxide C

International Regulations.

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Canadian WHMIS.

Information not available.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Ox. Liq. 3	Oxidising liquid, category 3
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
H272	May intensify fire; oxidiser.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%

MS68A - 68 Element Standard Part A 49 Elements in 2% Nitric Acid

- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.