

P62633 - Potassium Permanganate 0.891% w/v

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

Code: **P62633**
Product name **Potassium Permanganate 0.891% w/v**

1.2. Relevant identified uses of the substance or mixture and uses advised against
Intended use **For laboratory use only.****1.3. Details of the supplier of the safety data sheet**

Name **EXAXOL CHEMICAL CORPORATION**
Full address **14325 60 TH ST N**
District and Country **33760 CLEARWATER - FLORIDA**
US
Tel. **1-727-524-7732**
Fax **1-727-532-8221**

e-mail address

info@exaxol.com**1.4. Emergency telephone number**

For urgent inquiries refer to **1-800-255-3924**
ChemTel Inc.

2. Hazards identification

2.1. Classification of the substance or mixture

Hazard pictograms:

The product is not --
classified as hazardous
pursuant to the provisions
set forth in OSHA Hazard
Communication Standard
(HCS) (29 CFR
1910.1200). However,
since the product
contains hazardous
substances in
concentrations such as to
be declared in section no.
3, it requires a safety data
sheet with appropriate
information.

Signal words: --

P62633 - Potassium Permanganate 0.891% w/v

Hazard statements:

--

Precautionary statements:

Prevention:

--

Response:

--

Storage:

--

Disposal:

--

2.2. Other hazards

Environmental classification as for Reg. (EU) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 2

Toxic to aquatic life with long lasting effects.

Hazard pictograms:



Hazard statements:

--

H411

Toxic to aquatic life with long lasting effects.

Precautionary statements:

Prevention:

P273

Avoid release to the environment.

Response:

P391

Collect spillage.

Storage:

--

Disposal:

P501

Dispose of contents / container to an approved waste disposal plant.

Additional hazards

Information not available

3. Composition/information on ingredients**3.2. Mixtures**

P62633 - Potassium Permanganate 0.891% w/v

Contains:

Identification	Conc. %	Classification:
WATER		
CAS 7732-18-5	99.109	
EC 231-791-2		
INDEX -		
POTASSIUM PERMANGANATE		
CAS 7722-64-7	0.891	Oxidising solid, category 2 H272, Acute toxicity, category 4 H302, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=10, Hazardous to the aquatic environment, chronic toxicity, category 1 H410 M=10
EC 231-760-3		
INDEX 025-002-00-9		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

P62633 - Potassium Permanganate 0.891% w/v

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage**7.1. Precautions for safe handling**

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

P62633 - Potassium Permanganate 0.891% w/v

USA OSHA-PEL Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
 USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
 TLV-ACGIH ACGIH 2018

POTASSIUM PERMANGANATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH	-	0.1			
OSHA	USA			5 (C)	
OSHA	USA			5 (C)	
CAL/OSHA	USA	0.2			
CAL/OSHA	USA	0.2			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

Comply with the safety measures usually applied when handling chemical substances.

HAND PROTECTION

None required.

SKIN PROTECTION

None required.

EYE PROTECTION

None required.

RESPIRATORY PROTECTION

None required, unless indicated otherwise in the chemical risk assessment.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid
Colour	Not available
Odour	Not available
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available

P62633 - Potassium Permanganate 0.891% w/v

Boiling range	Not available
Flash point	> 93 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1.01
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Information not available

10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

POTASSIUM PERMANGANATE

Incompatible with: strong reducing agents,peroxides,zinc,copper,alcohols,hydrogen fluoride,acids,sulphuric acid,metal powders.

10.6. Hazardous decomposition products

Information not available

11. Toxicological information

P62633 - Potassium Permanganate 0.891% w/v

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled according to good industrial practices.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Does not meet the classification criteria for this hazard class

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

P62633 - Potassium Permanganate 0.891% w/v

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity**POTASSIUM PERMANGANATE**

LC50 - for Fish	0,96 mg/l/96h <i>Morone saxatilis</i>
EC50 - for Crustacea	0,084 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0,18 mg/l/72h <i>Aphanizomenon flos-aquae</i>

12.2. Persistence and degradability**POTASSIUM PERMANGANATE**

Solubility in water	> 10000 mg/l
Degradability: information not available	

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

P62633 - Potassium Permanganate 0.891% w/v**14. Transport information****14.1. UN number**

ADR / RID, IMDG, IATA:	3082
ADR / RID:	In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to ADR provisions.
IMDG:	In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IMDG Code provisions.
IATA:	In accordance with SP A197, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POTASSIUM PERMANGANATE)
IMDG:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POTASSIUM PERMANGANATE)
IATA:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POTASSIUM PERMANGANATE)

14.3. Transport hazard class(es)

ADR / RID:	Class: 9	Label: 9
IMDG:	Class: 9	Label: 9
IATA:	Class: 9	Label: 9

**14.4. Packing group**

P62633 - Potassium Permanganate 0.891% w/v

ADR / RID, IMDG, III
IATA:

14.5. Environmental hazards

ADR / RID: Environmentally
Hazardous



IMDG: Marine Pollutant



IATA: Environmentally
Hazardous

**14.6. Special precautions for user**

ADR / RID: HIN - Kemler: 90

Limited
Quantities: 5
L

Tunnel
restriction
code: (-)

IMDG: Special Provision: -
EMS: F-A, S-F

Limited
Quantities: 5
L

IATA: Cargo:

Maximum
quantity: 450
L

Packaging
instructions:
964

Pass.:

Maximum
quantity: 450
L

Packaging
instructions:
964

Special Instructions:

A97, A158,
A197

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**U.S. Federal RegulationsTSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

EXAXOL CHEMICAL CORPORATION

Revision nr. 1

Dated 5/10/2019

First compilation

Printed on 5/10/2019

Page n. 11/14

P62633 - Potassium Permanganate 0.891% w/v

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

EPA List of Lists:

313 Category Code:

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)

EPCRA 313 TRI:

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

P62633 - Potassium Permanganate 0.891% w/vState RegulationsMassachussets:

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)Minnesota:

No component(s) listed.

New Jersey:

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)New York:

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)Pennsylvania:

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)California:

7722-64-7

POTASSIUM PERMANGANATE
(Manganese compounds, Manganese
soluble compounds)Proposition 65:International RegulationsSubstances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Candadian WHMIS

Information not available

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

P62633 - Potassium Permanganate 0.891% w/v

H272	May intensify fire; oxidiser.
H302	Harmful if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website

P62633 - Potassium Permanganate 0.891% w/v

- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.