P62664 - Potassium Permanganate 0.5N

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 1/11

Safety data sheet according to U.S.A. Federal Hazcom 2012

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: P62664

Product name Potassium Permanganate 0.5N

1.2. Relevant identified uses of the substance or mixture and uses advised against

For Laboratory Use Only. Intended use

1.3. Details of the supplier of the safety data sheet

Name **EXAXOL CHEMICAL CORPORATION** Full address

14325 60 TH ST N

33760 CLEARWATER - FLORIDA District and Country

US

Tel. 1-727-524-7732 Fax 1-727-532-8221

e-mail address

info@exaxol.com

1.4. Emergency telephone number

1-800-255-3924 For urgent inquiries refer to

ChemTel Inc.

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information.

Signal words:

Hazard statements:

Precautionary statements:

P62664 - Potassium Permanganate 0.5N

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 2/11

Prevention:	_	
Response:		
Storage:		
Disposal:		
2.2. Other hazards.		
Environmental classification	n as for Reg. (EU) 1272/2008 (CLP):	
The product is classified as	s hazardous for environment pursuant to the provisions s	et forth in EC Regulation 1272/2008 (CLP).
Classification and Hazard S Hazardous to the aquatic		oxic to aquatic life with long lasting effects.

Hazard statements:		
H411	Toxic to aquatic life with long lasting effects.	
Precautionary statements:		
Prevention: P273	Avoid release to the environment.	
Response: P391	Collect spillage.	
Storage:		
Disposal: P501	Dispose of contents / container to an approved waste	disposal plant.
Additional hazards.		
SECTION 3. Com	position/information on ingredients.	
3.1. Substances.		
Information not relevant.		
3.2. Mixtures.		
Contains:		
Identification.	Conc. %. Class	ification:

WATER

P62664 - Potassium Permanganate 0.5N

50 - 100

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 3/11

POTASSIUM PERMANGANATE (37.76% -

metallic element)

CAS. 7732-18-5

CAS. 7722-64-7

1 - 2.5 Oxidising solid, category 2

H272, Acute toxicity, category 4 H302, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=10, Hazardous to the aquatic environment, chronic toxicity, category 1 H410

M = 10

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide and chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water.

Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 4/11

P62664 - Potassium Permanganate 0.5N

If large quantities of the product are involved in a fire, they can make it considerably worse. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

In the case of fire, use jets of water to cool the containers to prevent the risk of explosions (product decomposition and excess pressure) and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Remove all containers containing the product from the fire, if it is safe to do so.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

P62664 - Potassium Permanganate 0.5N

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 5/11

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

USA OSHA-PEL Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-

1910.1000.

USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA)

Permissible Exposure Limits (PELs).

TLV-ACGIH ACGIH 2014

POTASSIUM PERMANGANATE

I O I AGGIGINI I EKINANGA							
Threshold Limit Value.							
Туре	Country	TWA/8h		STEL/15min	STEL/15min		
		mg/m3	ppm	mg/m3	ppm		
TLV-ACGIH	-	0.1					
OSHA	USA			5 (C)			
OSHA	USA			5 (C)			
CAL/OSHA	USA	0.2					
CAL/OSHA	USA	0.2					

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

P62664 - Potassium Permanganate 0.5N

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 6/11

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance Not available. Not available Colour Odour Not available. Odour threshold. Not available. рН. Not available. Melting point / freezing point. Not available. Initial boiling point. Not available. Boiling range. Not available. Flash point. > 93 °C. Evaporation Rate Not available. Flammability of solids and gases Not available. Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available. Relative density. 1.010 Kg/l Solubility Not available. Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Decomposition temperature. Not available. Viscosity Not available. Explosive properties Not available. Oxidising properties Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

Information not available.

10.2. Chemical stability.

Information not available.

10.3. Possibility of hazardous reactions.

The product may react violently with water.

P62664 - Potassium Permanganate 0.5N

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 7/11

10.4. Conditions to avoid.

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This product may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.

11.1. Information on toxicological effects.

Information not available.

SECTION 12. Ecological information.

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment. **12.1. Toxicity.**

POTASSIUM PERMANGANATE

LC50 - for Fish. 0.96 mg/l/96h Morone saxatilis
EC50 - for Crustacea. 0.084 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic 0.18 mg/l/72h Aphanizomenon flos-aquae

Plants.

12.2. Persistence and degradability.

POTASSIUM PERMANGANATE Solubility in water

Solubility in water. > 10000 mg/l

Biodegradability: Information not available.

12.3. Bioaccumulative potential.

Information not available.

P62664 - Potassium Permanganate 0.5N

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 8/11

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

U.S. Federal Regulations.

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

7722-64-7

POTASSIUM PERMANGANATE (Manganese compounds, Manganese soluble compounds)

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act -

Priority Pollutants:

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 9/11

P62664 - Potassium Permanganate 0.5N

No component(s) listed. Clean Water Act -Toxic Pollutants: No component(s) listed. DEA List I Chemicals (Precursor Chemicals): No component(s) listed. DEA List II Chemicals (Essential Chemicals): EPA List of Lists: 313 Category Code: 7722-64-7 POTASSIUM PERMANGANATE (Manganese compounds, Manganese soluble compounds) POTASSIUM PERMANGANATE 7722-64-7 (Manganese compounds, Manganese soluble compounds) EPCRA 302 EHS TPQ: No component(s) listed. EPCRA 304 EHS RQ: No component(s) listed. CERCLA RQ: 7722-64-7 POTASSIUM PERMANGANATE (Manganese compounds, Manganese soluble compounds) EPCRA 313 TRI: 7722-64-7 POTASSIUM PERMANGANATE (Manganese compounds, Manganese soluble compounds) RCRA Code: No component(s) listed. CAA 112 (r) RMP TQ: No component(s) listed. State Regulations. Massachussetts: 7722-64-7 POTASSIUM PERMANGANATE

(Manganese compounds, Manganese soluble compounds)

Minnesota:

P62664 - Potassium Permanganate 0.5N

Revision nr. 1
Dated 11/9/2015

Printed on 9/11/2015

Page n. 10/11

No component(s) listed.

New Jersey:

7722-64-7 POTASSIUM PERMANGANATE

(Manganese compounds, Manganese

soluble compounds)

New York:

7722-64-7 POTASSIUM PERMANGANATE

(Manganese compounds, Manganese

soluble compounds)

Pennsylvania:

7722-64-7 POTASSIUM PERMANGANATE

(Manganese compounds, Manganese

soluble compounds)

California:

7722-64-7 POTASSIUM PERMANGANATE

(Manganese compounds, Manganese

soluble compounds)

Proposition 65:

International Regulations.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Candadian WHMIS.

Information not available.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H272 May intensify fire; oxidiser.
H302 Harmful if swallowed.
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

LEGEND:

Revision nr. 1

Dated 11/9/2015

Printed on 9/11/2015

Page n. 11/11

P62664 - Potassium Permanganate 0.5N

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- FPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control: therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.