PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

Revision nr. 1

Dated 3/8/2021

First compilation

Printed on 3/8/2021

Page n. 1/13

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

Code: PLCO₁

Product name Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

1.2. Relevant identified uses of the substance or mixture and uses advised against

For laboratory use only. Intended use

1.3. Details of the supplier of the safety data sheet

EXAXOL CHEMICAL CORPORATION

Full address 14325 60 TH ST N

33760 CLEARWATER - FLORIDA District and Country

Tel. 1-727-524-7732 Fax 1-727-532-8221

e-mail address

info@exaxol.com

1.4. Emergency telephone number

1-800-255-3924 For urgent inquiries refer to ChemTel Inc.

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Hazard pictograms:

Carcinogenicity, category 1B May cause cancer. Reproductive toxicity, category 1B May damage fertility or the unborn child. Eye irritation, category 2 Causes serious eve

irritation.

Skin irritation, category 2 Causes skin irritation. May cause allergy or Respiratory sensitization, category 1 asthma symptoms or

breathing difficulties if

inhaled.

Revision nr. 1

Dated 3/8/2021

First compilation

Printed on 3/8/2021

Page n. 2/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

Skin sensitization, category 1

May cause an allergic skin reaction.



Signal words: Danger

Hazard statements:

H350 May cause cancer.

May damage fertility or the unborn child. H360

H319 Causes serious eye irritation. H315 Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334

H317 May cause an allergic skin reaction.

Precautionary statements:

Prevention:

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P202 Do not handle until all safety precautions have been read and understood. P201 Obtain special instructions before use. Wear protective gloves/ protective clothing / eye protection / face protection. P280 P264 Wash skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. P284 [In case of inadequate ventilation] wear respiratory protection.

Response:

P272

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

P308+P313 IF exposed or concerned: Get medical advice / attention.

If experiencing respiratory symptoms: call a POISON CENTER / doctor. P342+P311

P333+P313 If skin irritation or rash occurs: Get medical advice / attention. P337+P313 If eye irritation persists: Get medical advice / attention.

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P302+P352 IF ON SKIN: wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents / container to an approved waste disposal plant.

2.2. Other hazards

Environmental classification as for Reg. (EU) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 3

Harmful to aquatic life with long lasting effects.

Hazard statements:

Revision nr. 1

Dated 3/8/2021

First compilation

Printed on 3/8/2021
Page n. 3/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

Harmful to aquatic life with long lasting effects.

Precautionary statements:

Prevention:

H412

P273 Avoid release to the environment.

Response:

-- '

Storage:

Disposal:

P501 Dispose of contents / container to an approved waste disposal plant.

Additional hazards

Corrosive to the respiratory tract.

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification Conc. % Classification:

WATER

CAS 7732-18-5 97.505

EC 231-791-2

INDEX -

NITRIC ACID

CAS 7697-37-2 2 Oxidising liquid, category 2 H272, Skin corrosion, category 1A H314, Serious

eye damage, category 1 H318

EC 231-714-2

INDEX 007-004-00-1

Cobalt(II) Nitrate Hexahydrate

CAS 10026-22-9 0.495 Oxidising solid, category 2 H272, Carcinogenicity, category 1B H350, Germ

cell mutagenicity, category 2 H341, Reproductive toxicity, category 1B H360, Acute toxicity, category 4 H302, Acute toxicity, category 4 H332, Serious eye damage, category 1 H318, Respiratory sensitization, category 1 H334, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1, Hazardous to the aquatic environment, chronic

toxicity, category 1 H410 M=1

EC

INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

Revision nr. 1

Dated 3/8/2021

First compilation
Printed on 3/8/2021

Page n. 4/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Revision nr. 1

Dated 3/8/2021

First compilation

Printed on 3/8/2021

Page n. 5/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA NIOSH-REL NIOSH publication No. 2005-149, 3th printing, 2007.

USA OSHA-PEL Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA) Permissible Expo

USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
U OEL EU Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2018

NITRIC ACID							
Threshold Limit Value							
Туре	Country	TWA/8h		STEL/15min			
		mg/m3	ppm	mg/m3	ppm		
TLV-ACGIH	-	5.2	2	10.3	4		
OEL	EU			2.6	1		
OSHA	USA	5	2				
CAL/OSHA	USA	5	2	10	4		
NIOSH	USA	5	2	10	4		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

Revision nr. 1

Dated 3/8/2021

First compilation

Printed on 3/8/2021

Page n. 6/13

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

HAND PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

liquid Appearance Colour Not available Odour Not available Odour threshold Not available Not available Melting point / freezing point Not available Initial boiling point Not available Not available Boiling range Flash point > 93 °C Evaporation Rate Not available Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Relative density 1 01 Not available Solubility Partition coefficient: n-octanol/water Not available Auto-ignition temperature Not available Decomposition temperature Not available Viscosity Not available Explosive properties Not available Oxidising properties Not available

9.2. Other information

Revision nr. 1

Dated 3/8/2021

First compilation

Printed on 3/8/2021

Page n. 7/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

Information not available

10. Stability and reactivity

10.1. Reactivity

NITRIC ACID

Decomposes at 84°C/183°F.Possibility of self-ignition.

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

NITRIC ACID

Avoid exposure to: heat, light.

10.5. Incompatible materials

NITRIC ACID

Incompatible with: flammable substances, reducing substances, alcohol, metals, basic substances, acetone, acetic acid, acetic anhydride. Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

NITRIC ACID

May develop: nitric oxide.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Revision nr. 1 Dated 3/8/2021

First compilation

Printed on 3/8/2021
Page n. 8/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

Metabolism, toxicokinetics, mechanism of action and other information Information not available Information on likely routes of exposure Information not available Delayed and immediate effects as well as chronic effects from short and long-term exposure Information not available Interactive effects Information not available **ACUTE TOXICITY** Corrosive to the respiratory tract. Cobalt(II) Nitrate Hexahydrate LD50 (Oral) 434 mg/kg NITRIC ACID LC50 (Inhalation) 67 ppm/4h Rat SKIN CORROSION / IRRITATION Causes skin irritation SERIOUS EYE DAMAGE / IRRITATION Causes serious eye irritation RESPIRATORY OR SKIN SENSITISATION Sensitising for the skin Sensitising for the respiratory system GERM CELL MUTAGENICITY

CARCINOGENICITY

May cause cancer

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Revision nr. 1

Dated 3/8/2021

First compilation
Printed on 3/8/2021

Page n. 9/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

May damage fertility or the unborn child

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

NITRIC ACID

Solubility in water > 1000000 mg/l

Degradability: information not available

12.3. Bioaccumulative potential

NITRIC ACID

Partition coefficient: n-octanol/water < 3

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

Revision nr. 1 Dated 3/8/2021

First compilation

Printed on 3/8/2021

Page n. 10/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information							
UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (Nitric acid 2%), 8, PG III							
15. Regulatory information							
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture							
U.S. Federal Regulations							
Clean Air Act Section 112(b):							
10026-22-9	Cobalt(II) Nitrate Hexahydrate (Cobalt compounds)						
Clean Air Act Section 602 Class I Substances:							
No component(s) listed.							
Clean Air Act Section 602 Class II Substances:							
No component(s) listed.							
Clean Water Act – Priority Pollutants:							
No component(s) listed.							
Clean Water Act – Toxic Pollutants:							
No component(s) listed.							
DEA List I Chemicals (Precursor Chemicals):							
No component(s) listed.							
DEA List II Chemicals (Essential Chemicals):							
No component(s) listed.							

EPA List of Lists:

313 Category Code:

7697-37-2 NITRIC ACID

10026-22-9 Cobalt(II) Nitrate Hexahydrate (Cobalt

Revision nr. 1

Dated 3/8/2021

First compilation

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

Printed on 3/8/2021
Page n. 11/13

compounds)

EPCRA 302 EHS TPQ:

7697-37-2 NITRIC ACID

EPCRA 304 EHS RQ:

7697-37-2 NITRIC ACID

CERCLA RQ:

7697-37-2 NITRIC ACID

EPCRA 313 TRI:

7697-37-2 NITRIC ACID

10026-22-9 Cobalt(II) Nitrate Hexahydrate (Cobalt

compounds)

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussetts:

7697-37-2 NITRIC ACID

Minnesota:

7697-37-2 NITRIC ACID

New Jersey:

7697-37-2 NITRIC ACID

10026-22-9 Cobalt(II) Nitrate Hexahydrate (Cobalt

compounds)

New York:

7697-37-2 NITRIC ACID

Pennsylvania:

7697-37-2 NITRIC ACID

10026-22-9 Cobalt(II) Nitrate Hexahydrate (Cobalt

compounds)

California:

7697-37-2 NITRIC ACID

Proposition 65:

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

Revision nr. 1 Dated 3/8/2021

First compilation
Printed on 3/8/2021

Page n. 12/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Candadian WHMIS

Information not available

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H272 May intensify fire; oxidiser.

H350 May cause cancer.

H341 Suspected of causing genetic defects.H360 May damage fertility or the unborn child.

H302 Harmful if swallowed.
H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H315 Causes skin irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- · CE50: Effective concentration (required to induce a 50% effect)
- · CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%

Revision nr. 1

Dated 3/8/2021

First compilation

Printed on 3/8/2021

Page n. 13/13

PLCO1 - Cobalt 1,000 ppm ICP Standard in 2% Nitric Acid

- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- FPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.