EXAXOL CH	IEMICAL CORPORATION	Revision nr. 1 Dated 9/9/2015
S65722 - Sodium Chromate 2% w/v		Printed on 9/9/2015
		Page n. 1/12
2	et according to U.S.A. Fede	
4.4. Des dust identifier		
1.1. Product identifier Code:	S65722	
Product name	Sodium Chromate 2% w/v	
<b>1.3. Details of the supplier of the safety dat</b> Name Full address District and Country e-mail address	a sheet EXAXOL CHEMICAL CORPORATION 14325,60 TH ST N 33760 CLEARWATER - FLORIDA US Tel. 1-727-524-7732 Fax 1-727-532-8221	
	info@exaxol.com	
<b>1.4. Emergency telephone number</b> For urgent inquiries refer to	1-800-255-3924 ChemTel Inc.	
SECTION 2. Hazards identificat	ion.	
2.1. Classification of the substance or mixt	ure.	

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement. Carcinogenicity, category 1B Germ cell mutagenicity, category 1B Reproductive toxicity, category 1B Acute toxicity, category 4 Specific target organ toxicity - repeated exposure, category 1 Eye irritation, category 2 Skin irritation, category 2 Respiratory sensitization, category 1 Skin sensitization, category 1

May cause cancer. May cause genetic defects. May damage fertility or the unborn child. Harmful if inhaled. Causes damage to organs through prolonged or repeated exposure. Causes serious eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Signal words:

Danger

Revision nr. 1

## S65722 - Sodium Chromate 2% w/v

Dated 9/9/2015

Printed on 9/9/2015 Page n. 2/12

Hazard statements:

Hazard statements:	
H350 H340 H360 H332 H372 H319 H315 H334 H317	May cause cancer. May cause genetic defects. May damage fertility or the unborn child. Harmful if inhaled. Causes damage to organs through prolonged or repeated exposure. Causes serious eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Precautionary statements:	
Prevention: P201 P202 P260 P264 P270 P271 P272 P280 P284 Response: P302+P352 P304+P340 P305+P351+P338 P321 P362+P364 Storage: P405 Disposal:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust / fume / gas / mist / vapours / spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves / protective clothing / eye protection / face protection. In case of inadequate ventilation wear respiratory protection. IF ON SKIN: wash with plenty of water. IF INHALED: remove person to fresh air and keep comfortable for breathing. IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see label). Take off contaminated clothing and wash it before reuse. Store locked up.
P501	Dispose of contents / container to an approved waste disposal plant.
2.2. Other hazards. Environmental classification	as for Reg. (EU) 1272/2008 (CLP):
The product is classified as	hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).
	tatement. environment, chronic toxicity, category 3 Harmful to aquatic life with long lasting effects.
Hazard statements:	
H412	Harmful to aquatic life with long lasting effects.
Precautionary statements:	
Prevention: P273 Response:	Avoid release to the environment.
 Storage:  Disposal: <b>P501</b> 	Dispose of contents / container to an approved waste disposal plant.

EXAXOL CHEMICAL CORPORATION	Revision nr. 1 Dated 9/9/2015
S65722 - Sodium Chromate 2% w/v	Printed on 9/9/2015 Page n. 3/12

Additional hazards.

## SECTION 3. Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification:
WATER		
CAS. 7732-18-5	50 - 100	
Sodium Chromate		
CAS. 7775-11-3	1 - 2.5	Carcinogenicity, category 1B H350, Germ cell mutagenicity, category 1B H340, Reproductive toxicity, category 1B H360, Acute toxicity, category 2 H330, Acute toxicity, category 3 H301, Acute toxicity, category 4 H312, Specific target organ toxicity - repeated exposure, category 1 H372, Skin corrosion, category 1B H314, Respiratory sensitization, category 1 H334, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1, Hazardous to the aquatic environment, chronic toxicity, category 1 H410

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures.**

#### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed.

EXAXOL CHEMICAL CORPORATION	Revision nr. 1
	Dated 9/9/2015
S65722 - Sodium Chromate 2% w/v	Printed on 9/9/2015
	Page n. 4/12

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

#### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6.** Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Revision nr. 1

## S65722 - Sodium Chromate 2% w/v

Dated 9/9/2015

Printed on 9/9/2015 Page n. 5/12

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

### **SECTION 7. Handling and storage.**

#### 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s).

Information not available.

### **SECTION 8. Exposure controls/personal protection.**

#### 8.1. Control parameters.

Information not available.

#### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must comply with current regulations.

Provide an emergency shower with face and eye wash station.

The product must be used inside a closed circuit, in a well-ventilated environment and with strong localised aspiration systems in place.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138). The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap

Revision nr. 1

## S65722 - Sodium Chromate 2% w/v

Dated 9/9/2015 Printed on 9/9/2015

Page n. 6/12

and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

## **SECTION 9.** Physical and chemical properties.

#### 9.1. Information on basic physical and chemical properties.

Appeorance	Not available.
Appearance Colour	Not available.
Odour	Not available.
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	> 93 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1.013 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

#### 9.2. Other information.

Information not available.

## **SECTION 10. Stability and reactivity.**

S65722 - Sodium Chromate 2% w/v

Revision nr. 1 Dated 9/9/2015

Printed on 9/9/2015

Page n. 7/12

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials.

Information not available.

#### 10.6. Hazardous decomposition products.

Information not available.

## **SECTION 11. Toxicological information.**

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product should be considered carcinogenic for human beings. Currently available data suggest that human exposure to the substance contained in this product may give rise to cancer development.

This product may have a mutagenic effect on human beings. Currently available data may suggest that human exposure to the substance contained in this product may give rise to the development of hereditary gene alterations.

This product has a teratogenic effect on human beings: damages fertility and/or has toxic effects on fetus development.

There is sufficient evidence to make us believe that the substance contained in the product is likely to affect the embryo-fetal development and/or the fetus development.

Acute effects: inhalation of this product is harmful.

Exposure symptoms may include: stinging and irritated eyes, mouth, nose, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness. In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema and irritation, chemical pneumonia and pulmonary edema.

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human body and is thus graded as dangerous.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin.

Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and

Revision nr. 1

## S65722 - Sodium Chromate 2% w/v

Dated 9/9/2015

Printed on 9/9/2015 Page n. 8/12

affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma. Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

## **SECTION 12. Ecological information.**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment. **12.1. Toxicity.** 

Information not available.

### 12.2. Persistence and degradability.

Information not available.

### 12.3. Bioaccumulative potential.

Information not available.

### 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.

Information not available.

## **SECTION 13.** Disposal considerations.

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information.**

## **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

EXAXOL CHEMICAL CORPORATION	Revision nr. 1
	Dated 9/9/2015 Printed on 9/9/2015
S65722 - Sodium Chromate 2% w/v	Page n. 9/12
U.S. Federal Regulations.	
TSCA:	
All components are listed on TSCA Inventory.	
Clean Air Act Section 112(b):	
No component(s) listed.	
Clean Air Act Section 602 Class I Substances:	
No component(s) listed.	
Clean Air Act Section 602 Class II Substances:	
No component(s) listed.	
Clean Water Act – Priority Pollutants:	
No component(s) listed.	
<u>Clean Water Act – Toxic Pollutants:</u>	
No component(s) listed.	
DEA List I Chemicals (Precursor Chemicals):	
No component(s) listed.	
DEA List II Chemicals (Essential Chemicals):	
No component(s) listed.	
EPA List of Lists:	
313 Category Code:	
No component(s) listed.	
EPCRA 302 EHS TPQ:	
No component(s) listed.	
EPCRA 304 EHS RQ:	
No component(s) listed.	

CERCLA RQ:

No component(s) listed.

EXAXOL CHEMICAL CORPORATION		Revision nr. 1 Dated 9/9/2015
S65722 - Sodiur	n Chromate 2% w/v	Printed on 9/9/2015 Page n. 10/12
EPCRA 313 TRI:		
No component(s) listed.		
RCRA Code:		
No component(s) listed.		
CAA 112 (r) RMP TQ:		
No component(s) listed.		
State Regulations.		
Massachussetts:		
7775-11-3	Sodium Chromate	
Minnesota:		
No component(s) listed.		
New Jersey:		
7775-11-3	Sodium Chromate	
New York:		
7775-11-3	Sodium Chromate	
Pennsylvania:	Quality Observation	
7775-11-3 <u>California:</u>	Sodium Chromate	
7775-11-3	Sodium Chromate	
Proposition 65:		
nternational Regulations.		
Substances subject to exportation reporting pursuant to	(EC) Reg. 649/2012:	
None.		
Substances subject to the Rotterdam Convention:		
None.		
Substances subject to the Stockholm Convention:		
None.		
Candadian WHMIS.		
nformation not available.		

S65722 - Sodium Chromate 2% w/v

Revision nr. 1

Dated 9/9/2015 Printed on 9/9/2015

Page n. 11/12

## **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 1B	Carcinogenicity, category 1B
Muta. 1B	Germ cell mutagenicity, category 1B
Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic toxicity, category 4
H350	May cause cancer.
H340	May cause genetic defects.
H360	May damage fertility or the unborn child.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code - ADR: European Agreement concerning the carriage of Dangerous goods by Road

S65722 - Sodium Chromate 2% w/v

Revision nr. 1 Dated 9/9/2015

Dated

## Printed on 9/9/2015 Page n. 12/12

	1 ugo 11. 12/12
	•
CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)	
CAS NUMBER: Chemical Abstract Service Number	
CE50: Effective concentration (required to induce a 50% effect)	
CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)	
CLP: EC Regulation 1272/2008	
DEA: Drug Enforcement Administration	
EmS: Emergency Schedule EPA: US Environmental Protection Agency	
EPCRA: Emergency Planning and Community Right-to Know Act	
EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code	e)
EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)	- )
EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)	
GHS: Globally Harmonized System of classification and labeling of chemicals	
ATA DGR: International Air Transport Association Dangerous Goods Regulation	
C50: Immobilization Concentration 50%	
IMDG: International Maritime Code for dangerous goods IMO: International Maritime Organization	
LC50: Lethal Concentration 50%	
LD50: Lethal dose 50%	
OEL: Occupational Exposure Level	
PEL: Predicted exposure level	
RCRA Code: Resource Conservation and Recovery Act Code	
REL: Recommended exposure limit	
RID: Regulation concerning the international transport of dangerous goods by train	
TLV: Threshold Limit Value TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.	
TSCA: Toxic Substances Control Act	
TWA STEL: Short-term exposure limit	
TWA: Time-weighted average exposure limit	
VOC: Volatile organic Compounds	
WHMIS: Workplace Hazardous Materials Information System.	
ENERAL BIBLIOGRAPHY:	
GHS rev. 3	
The Merck Index. 10th Edition Handling Chemical Safety	
Niosh - Registry of Toxic Effects of Chemical Substances	
INRS - Fiche Toxicologique (toxicological sheet)	
Patty - Industrial Hygiene and Toxicology	
N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition	
ECHA website	
6 NYCRR part 597	
Cal/OSHA website	
California Safe Drinking Water and Toxic Enforcement Act EPA website	
Hazard Comunication Standard (HCS 2012)	
IARC website	
List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air	Act
Massachussetts 105 CMR Department of public health 670.000: "Right to Know"	
Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".	
New Jersey Worker and Community Right to know Act N.J.S.A.	
NTP. 2011. Report on Carcinogens, 12th Edition.	
OSHA website Representational Hazardoure Substance List. Chapter 222	
Pennsylvania, Hazardous Substance List, Chapter 323 ote for users:	
he information contained in the present sheet are based on our own knowledge on the date of the last version.	Users must verify the suitability and
oroughness of provided information according to each specific use of the product.	
his document must not be regarded as a guarantee on any specific product property.	
he use of this product is not subject to our direct control; therefore, users must, under their own responsibility, com	nply with the current health and safety
ws and regulations. The producer is relieved from any liability arising from improper uses.	
rovide appointed staff with adequate training on how to use chemical products.	