Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 1/12

SP61520 - PAN Indicator 0.1% w/v in Methanol

Safety data sheet according to U.S.A. Federal Hazcom 2012

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: SP61520

Product name PAN Indicator 0.1% w/v in Methanol

1.2. Relevant identified uses of the substance or mixture and uses advised against

For Laboratory Use Only. Intended use

1.3. Details of the supplier of the safety data sheet

EXAXOL CHEMICAL CORPORATION Name Full address

14325 60 TH ST N

33760 CLEARWATER - FLORIDA District and Country

US

Tel. 1-727-524-7732 Fax 1-727-532-8221

e-mail address

info@exaxol.com

1.4. Emergency telephone number

1-800-255-3924 For urgent inquiries refer to ChemTel Inc.

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement.

Flammable liquid, category 2 Acute toxicity, category 3

Specific target organ toxicity - single exposure, category 1

Highly flammable liquid and vapour. Toxic if swallowed, in contact with skin or if inhaled. Causes damage to organs.







Signal words:

Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

SP61520 - PAN Indicator 0.1% w/v in Methanol

Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 2/12

Causes damage to organs.

Precautionary statements:

Prevention:

H370

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / lighting / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

Response:

P302+P352 IF ON SKIN: wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P321 Specific treatment (see label).

P330 Rinse mouth.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.
P370+P378 In case of fire: use dry dand, dry chemical or alcohol-resistant foam extinguish.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents / container to an approved waste disposal plant.

2.2. Other hazards.

The product is not classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification. Conc. %. Classification:

METHANOL

CAS. 67-56-1 50 - 100 Flammable liquid, category 2

H225, Acute toxicity, category 3 H301, Acute toxicity, category 3 H311, Acute toxicity, category 3 H331, Specific target organ toxicity single exposure, category 1

H370

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 3/12

SP61520 - PAN Indicator 0.1% w/v in Methanol

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 4/12

SP61520 - PAN Indicator 0.1% w/v in Methanol

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

SP61520 - PAN Indicator 0.1% w/v in Methanol

Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 5/12

USA NIOSH-REL NIOSH publication No. 2005-149, 3th printing, 2007.

USA OSHA-PEL Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-

1910.1000.

USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA)

Permissible Exposure Limits (PELs).

EU OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC;

Directive 2000/39/EC.

TLV-ACGIH ACGIH 2014

METHANOL Threshold Limit Value. Country TWA/8h STEL/15min mg/m3 mg/m3 ppm ppm OEL SKIN EU 260 200 TI V-ACGIH 262 200 328 250 OSHA LISA 260 200 CAL/OSHA USA 260 200 1000 (C) SKIN 325 (C) NIOSH USA 260 200 325 250 SKIN.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must comply with current regulations.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose limit of use will be defined by the manufacturer (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

Revision nr. 1
Dated 14/11/2016

Printed on 11/14/2016

Page n. 6/12

SP61520 - PAN Indicator 0.1% w/v in Methanol

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance Not available. Colour Not available. Odour Not available. Odour threshold. Not available. Not available. Melting point / freezing point. Initial boiling point. Not available. > 35 °C. Not available. Boiling range. Flash point. < 23 °C. Evaporation Rate Not available. Flammability of solids and gases Not available. Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available. Relative density. Not available. Solubility Not available. Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Decomposition temperature. Not available. Viscosity Not available. Explosive properties Not available. Oxidising properties Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid.

Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 7/12

SP61520 - PAN Indicator 0.1% w/v in Methanol

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: this product is toxic and causes poisoning by inhalation, cutaneous absorption and ingestion. Poisoning by inhalation may give rise to a series of symptoms, which may include: stinging and irritared eyes, mouth, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness. In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema, chemical pneumonia and pulmonary edema, reduction or increase of heart-beat, copious salivation, blood sputum, loss of consciousness, behavioral disorders (depression or euphoria). Poisoning by cutaneous absorption may give rise to symptoms, which may include: increase of skin temperature, swelling, itchiness, headache, respiratory disorders and sometimes even burns and cauterizations. Ingestion of even small amounts of product may cause serious health problems and symptoms such as mouth and throat burns or lesions, nausea, stomach pain, sickness, diarrhoea, sudoresis, convulsions, loss of consciousness.

This product may cause irreversible, serious, non-lethal damages after one single exposure by inhalation.

It may also cause irreversible, very serious, non-lethal damages after a single exposure by cutaneous absorption.

METHANOL: The minimal lethal dose following ingestion is considered to be in the range of 300-1000 mg/kg. Ingestion of as little as 4-10 ml methanol in adults may cause permanent blindness (IPCS).

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

METHANOL

Solubility in water.

ma/l 1000 - 10000

Rapidly biodegradable.

12.3. Bioaccumulative potential.

METHANOL

Revision nr. 1

Dated 14/11/2016

Dated 14/11/2016

Printed on 11/14/2016

Page n. 8/12

SP61520 - PAN Indicator 0.1% w/v in Methanol

Partition coefficient: n-octanol/water.

-0.77

octanol/wate BCF.

0.2

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to dangerous goods transport regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

UN: 1230

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG,

IATA:

14.2. UN proper shipping name.

ADR / RID: METHANOL SOLUTION IMDG: METHANOL SOLUTION

IATA:

14.3. Transport hazard class(es).

ADR / RID: Class: 3 Label: 3 (6.1)

IMDG: Class: 3 Label: 3 (6.1)

IATA: Class: 3 Label: 3 (6.1)





SP61520 - PAN Indicator 0.1% w/v in Methanol

Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 9/12

14.4. Packing group.

ADR / RID, IMDG,

Ш

IATA:

14.5. Environmental hazards.

ADR / RID:

IATA:

NO

14.6. Special precautions for user.

ADR / RID: Nr. Kemler: 336

Limited Quantity 1 L

restriction code (D/E)

Tunnel

Special Provision: -

IMDG: EMS: F-E, S-D

Cargo:

Quantity 1 L

Limited

Maximum Packaging quantity: 60 L instructions:

364

Pass.:

Maximum quantity: 1 L

Packaging instructions:

352

Special Instructions:

A104, A113

•

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

U.S. Federal Regulations.

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

67-56-1 METHANOL

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 10/12

SP61520 - PAN Indicator 0.1% w/v in Methanol

No component(s) listed.	
Clean Water Act – Toxic Pollutants:	
No component(s) listed.	
DEA List I Chemicals (Precursor Chemicals):	
No component(s) listed.	
DEA List II Chemicals (Essential Chemicals):	
No component(s) listed.	
EPA List of Lists:	
313 Category Code:	
67-56-1 EPCRA 302 EHS TPQ:	METHANOL
No component(s) listed.	
EPCRA 304 EHS RQ:	
No component(s) listed.	
CERCLA RQ:	
67-56-1 EPCRA 313 TRI:	METHANOL
67-56-1 RCRA Code:	METHANOL
67-56-1 CAA 112 (r) RMP TQ:	METHANOL
No component(s) listed.	
State Regulations.	
Massachussetts:	
67-56-1 Minnesota:	METHANOL
67-56-1 <u>New Jersey:</u>	METHANOL
67-56-1	METHANOL

SP61520 - PAN Indicator 0.1% w/v in Methanol

Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 11/12

New York:

67-56-1 METHANOL

Pennsylvania:

67-56-1 METHANOL

California:

67-56-1 METHANOL

Proposition 65:

WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

67-56-1 METHANOL D

International Regulations.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Candadian WHMIS.

Information not available.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2
Acute Tox. 3 Acute toxicity, category 3

STOT SE 1 Specific target organ toxicity - single exposure, category 1

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H370 Causes damage to organs.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule

Revision nr. 1

Dated 14/11/2016

Printed on 11/14/2016

Page n. 12/12

SP61520 - PAN Indicator 0.1% w/v in Methanol

- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
 EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.