

**SS6524 - Sodium Hydroxide Pellets**

# Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

## 1. Identification

### 1.1. Product identifier

Code: **SS6524**  
Product name: **Sodium Hydroxide Pellets**  
CAS number: **1310-73-2**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **For laboratory use only.**

### 1.3. Details of the supplier of the safety data sheet

Name: **EXAXOL CHEMICAL CORPORATION**  
Full address: **14325 60 TH ST N**  
District and Country: **33760 CLEARWATER - FLORIDA**  
**US**  
Tel. **1-727-524-7732**  
Fax **1-727-532-8221**

e-mail address

**info@exaxol.com**

### 1.4. Emergency telephone number

For urgent inquiries refer to **1-800-255-3924**  
**ChemTel Inc.**

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Hazard pictograms:

Substance or mixture corrosive to metals, category 1	May be corrosive to metals.
Skin corrosion, category 1	Causes severe skin burns and eye damage.
Serious eye damage, category 1	Causes serious eye damage.

**SS6524 - Sodium Hydroxide Pellets**

Signal words:                    Danger

Hazard statements:

**H290**                                May be corrosive to metals.  
**H314**                                Causes severe skin burns and eye damage.

Precautionary statements:

Prevention:

**P260**                                Do not breathe dust / fume / gas / mist / vapours / spray.  
**P234**                                Keep only in original container.  
**P280**                                Wear protective gloves/ protective clothing / eye protection / face protection.  
**P264**                                Wash skin thoroughly after handling.

Response:

**P305+P351+P338**                IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P301+P330+P331**                IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
**P303+P361+P353**                IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.  
**P310**                                    Immediately call a POISON CENTER / doctor.  
**P304+P340**                        IF INHALED: remove person to fresh air and keep comfortable for breathing.  
**P390**                                    Absorb spillage to prevent material damage.  
**P363**                                    Wash contaminated clothing before reuse.

Storage:

**P405**                                    Store locked up.

Disposal:

**P501**                                    Dispose of contents / container to an approved waste disposal plant.

## 2.2. Other hazards

Information not available

## 3. Composition/information on ingredients

### 3.1. Substances

Contains:

Identification	Conc. %	Classification:
<b>SODIUM HYDROXIDE</b>		
CAS 1310-73-2	100	Substance or mixture corrosive to metals, category 1 H290, Skin corrosion, category 1A H314, Serious eye damage, category 1 H318
EC 215-185-5		
INDEX 011-002-00-6		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## 4. First-aid measures

**SS6524 - Sodium Hydroxide Pellets****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

**4.2. Most important symptoms and effects, both acute and delayed**

Information not available

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**5. Fire-fighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**SS6524 - Sodium Hydroxide Pellets****6.3. Methods and material for containment and cleaning up**

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**7. Handling and storage****7.1. Precautions for safe handling**

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available

**8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
	TLV-ACGIH	ACGIH 2018

**SODIUM HYDROXIDE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH	-			2 (C)	
OSHA	USA	2			
CAL/OSHA	USA	2			
NIOSH	USA			2 (C)	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

## SS6524 - Sodium Hydroxide Pellets

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

### HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (OSHA 29 CFR 1910.138). Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

### RESPIRATORY PROTECTION

None required, unless indicated otherwise in the chemical risk assessment.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	solid
Colour	white
Odour	Not available
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not applicable
Boiling range	Not available
Flash point	Not applicable
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1.34
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

### 9.2. Other information

Information not available

## 10. Stability and reactivity

**SS6524 - Sodium Hydroxide Pellets****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**10.4. Conditions to avoid**

None in particular. However the usual precautions used for chemical products should be respected.

Avoid exposure to: air,moisture,sources of heat.

**10.5. Incompatible materials**

Incompatible with: strong acids,ammonia,zinc,lead,aluminium,water,flammable liquids.

**10.6. Hazardous decomposition products**

Information not available

**11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

**SS6524 - Sodium Hydroxide Pellets**

Information not available

ACUTE TOXICITY

## SODIUM HYDROXIDE

LD50 (Oral) 1350 mg/kg Rat

LD50 (Dermal) 1350 mg/kg Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or

**SS6524 - Sodium Hydroxide Pellets**

contaminate soil or vegetation.

**12.1. Toxicity**

Information not available

**12.2. Persistence and degradability**

SODIUM HYDROXIDE

Solubility in water > 10000 mg/l

Degradability: information not available

**12.3. Bioaccumulative potential**

Information not available

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**14. Transport information****14.1. UN number**

ADR / RID, IMDG, 1823  
IATA:

**14.2. UN proper shipping name**

ADR / RID: SODIUM HYDROXIDE, SOLID  
IMDG: SODIUM HYDROXIDE, SOLID  
IATA: SODIUM HYDROXIDE, SOLID



**SS6524 - Sodium Hydroxide Pellets**

**14.3. Transport hazard class(es)**

ADR / RID:            Class: 8            Label: 8  
 IMDG:                Class: 8            Label: 8  
 IATA:                 Class: 8            Label: 8



**14.4. Packing group**

ADR / RID, IMDG,    II  
 IATA:

**14.5. Environmental hazards**

ADR / RID:            NO  
 IMDG:                NO  
 IATA:                 NO

**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: 80	Limited Quantities: 1 kg	Tunnel restriction code: (E)
	Special Provision: -		
IMDG:	EMS: F-A, S-B	Limited Quantities: 1 kg	
IATA:	Cargo:	Maximum quantity: 50 Kg	Packaging instructions: 863
	Pass.:	Maximum quantity: 15 Kg	Packaging instructions: 859
	Special Instructions:	-	

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

U.S. Federal Regulations

TSCA:

All components are listed on TSCA Inventory.

**SS6524 - Sodium Hydroxide Pellets**

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act –  
Priority Pollutants:

No component(s) listed.

Clean Water Act –  
Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

No component(s) listed.

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

1310-73-2

SODIUM HYDROXIDE

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

**SS6524 - Sodium Hydroxide Pellets**

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussets:

1310-73-2 SODIUM HYDROXIDE

Minnesota:

1310-73-2 SODIUM HYDROXIDE

New Jersey:

1310-73-2 SODIUM HYDROXIDE

New York:

1310-73-2 SODIUM HYDROXIDE

Pennsylvania:

1310-73-2 SODIUM HYDROXIDE

California:

1310-73-2 SODIUM HYDROXIDE

Proposition 65:

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Candadian WHMIS

Information not available

**16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

**SS6524 - Sodium Hydroxide Pellets**

<b>H290</b>	May be corrosive to metals.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.

## LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 @ RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112@)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

## GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112@ of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

**SS6524 - Sodium Hydroxide Pellets**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.