EXAXOL C	HEMICAL CORPORATION	Revision nr. 1 Dated 14/1/2016
T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol		Printed on 1/14/2016
		Page n. 1/11
Safety data she	et according to U.S.A. Federal	Hazcom 2012
SECTION 1. Identification of th	e substance/mixture and of the company/un	dertaking
<b>1.1. Product identifier</b> Code: Product name	T7022 Thymolphthalein 0.1% w/v Indicator in 50% Ethanol	
1.2. Relevant identified uses of the substate Intended use For Laborate	ance or mixture and uses advised against ory Use Only.	
<b>1.3. Details of the supplier of the safety da</b> Name Full address District and Country	ata sheet EXAXOL CHEMICAL CORPORATION 14325 60 TH ST N 33760 CLEARWATER - FLORIDA US	
	Tel. 1-727-524-7732	
	Fax 1-727-532-8221	
e-mail address	info@exaxol.com	
<b>1.4. Emergency telephone number</b> For urgent inquiries refer to	1-800-255-3924 ChemTel Inc.	
SECTION 2. Hazards identifica	tion.	
2.1. Classification of the substance or mix	cture.	

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement. Flammable liquid, category 2 Carcinogenicity, category 1A



Signal words:

Danger

Hazard statements:

H225 H350 Highly flammable liquid and vapour. May cause cancer. Highly flammable liquid and vapour. May cause cancer.

Revision nr. 1

# T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol

Dated 14/1/2016

Printed on 1/14/2016 Page n. 2/11

Precautionary statements:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground / bond container and receiving equipment.
Use explosion-proof electrical / ventilating / lighting /equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves / protective clothing / eye protection / face protection.
IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.
IF exposed or concerned: get medical advice.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents / container to an approved waste disposal plant.

2.2. Other hazards.

The product is not classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

## **SECTION 3.** Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification:
ETHANOL		
CAS. 64-17-5	50 - 100	Flammable liquid, category 2 H225, Carcinogenicity, category 1A H350
CAS. 7732-18-5	30 - 50	

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures.**

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

Revision nr. 1

Page n. 3/11

## T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol

Dated 14/1/2016

Printed on 1/14/2016

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately. INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

### **SECTION 5. Firefighting measures.**

#### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6.** Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

Revision nr. 1

## T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol

Dated 14/1/2016

Printed on 1/14/2016 Page n. 4/11

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage.**

#### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s).

Information not available.

### **SECTION 8.** Exposure controls/personal protection.

#### 8.1. Control parameters.

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1- 1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
	TLV-ACGIH	ACGIH 2014

Revision nr. 1

## T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol

Dated 14/1/2016

Printed on 1/14/2016 Page n. 5/11

ETHANOL						
Threshold Limit Value.						
Туре	Country	TWA/8h	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-			1884	1000	
OSHA	USA	1900	1000			
CAL/OSHA	USA	1.9	1			
NIOSH	USA	1900	1000			

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must comply with current regulations.

Provide an emergency shower with face and eye wash station.

The product must be used inside a closed circuit, in a well-ventilated environment and with strong localised aspiration systems in place.

### HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose limit of use will be defined by the manufacturer (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## **SECTION 9.** Physical and chemical properties.

#### 9.1. Information on basic physical and chemical properties.

Appearance Colour Not available. Not available.

Revision nr. 1

Page n. 6/11

## T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol

Not available. Not available. Not available. Not available. > 35 °C. Not available. < 23 °C. Not available. Not available. Not available Not available. Not available.

Dated 14/1/2016

Printed on 1/14/2016

Odour
Odour threshold.
pH.
Melting point / freezing point.
Initial boiling point.
Boiling range.
Flash point.
Evaporation Rate
Flammability of solids and gases
Lower inflammability limit.
Upper inflammability limit.
Lower explosive limit.
Upper explosive limit.
Vapour pressure.
Vapour density
Relative density.
Solubility
Partition coefficient: n-octanol/water
Auto-ignition temperature.
Decomposition temperature.
Viscosity
Explosive properties
Oxidising properties

### 9.2. Other information.

Information not available.

## **SECTION 10. Stability and reactivity.**

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

ETHANOL: risk of explosion on contact with: alkaline metals, alkaline oxides, calcium hypochlorite, sulphur monofluoride, acetic anhydride (with acids), concentrated hydrogen peroxide, perchlorates, perchloric acid, perchloronitrile, mercury nitrate, nitric acid, silver and nitric acid, silver nitrate, silver nitrate and ammonia, silver oxide and ammonia, strong oxidising agents, nitrogen dioxide. Can react dangerously with: bromoacetylene, chlorine acetylene, bromine trifluoride, chromium trioxide, chromyl chloride, oxiranes, fluorine, potassium tert-butoxide, lithium hydride, phosphorus trioxide, black platinum, zirconium (IV) chloride, zirconium (IV) iodide. Forms an explosive mixture with the air.

### 10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHANOL: avoid exposure to sources of heat and naked flames.

Revision nr. 1

Page n. 7/11

# T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol

Dated 14/1/2016

Printed on 1/14/2016

10.5. Incompatible materials.

Information not available.

### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## **SECTION 11. Toxicological information.**

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product. This product has a carcinogenic effect on human beings. Currently available data suggest a cause-effect relationship between human exposure to the substance contained in this product and cancer development.

ETHANOL LD50 (Oral).> 5000 mg/kg Rat LC50 (Inhalation).120 mg/l/4h Pimephales promelas

Carcinogenicity Assessment:64-17-5ETHANOL ACGIH:: A3 IARC:1

## **SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

12.1. Toxicity. Information not available.

12.2. Persistence and degradability.

ETHANOL Solubility in water.

mg/l 1000 - 10000

Rapidly biodegradable.

12.3. Bioaccumulative potential.

**ETHANOL** 

Partition coefficient: noctanol/water.

-0.35

Revision nr. 1

Page n. 8/11

# T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol

Dated 14/1/2016

Printed on 1/14/2016

12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

## **SECTION 13.** Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information.**

## **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

U.S. Federal Regulations.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

<u>Clean Water Act –</u> Priority Pollutants:

No component(s) listed.

<u>Clean Water Act –</u> Toxic Pollutants:

# T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol

Revision nr. 1 Dated 14/1/2016

# Printed on 1/14/2016

Page n. 9/11

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

No component(s) listed.

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations.

Massachussetts:

64-17-5

ETHANOL

ETHANOL

ETHANOL

Minnesota:

64-17-5

New Jersey:

64-17-5 <u>New York:</u>

EXAXOL CHEMICAL CORPORATION	Revision nr. 1
	Dated 14/1/2016
T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol	Printed on 1/14/2016
	Page n. 10/11

No component(s) listed.	
Pennsylvania:	
64-17-5 <u>California:</u>	ETHANOL
64-17-5 Proposition 65:	ETHANOL
International Regulations.	
Substances subject to exportation reporting pursuant to (EC) R	eg. 649/2012:
None.	
Substances subject to the Rotterdam Convention:	
None.	
Substances subject to the Stockholm Convention:	
None.	
Candadian WHMIS.	
Information not available.	

## **SECTION 16.** Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Carc. 1A	Carcinogenicity, category 1A
H225	Highly flammable liquid and vapour.
H350	May cause cancer.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code) GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization

Revision nr. 1

# T7022 - Thymolphthalein 0.1% w/v Indicator in 50% Ethanol

Dated 14/1/2016

Printed on 1/14/2016 Page n. 11/11

- LC50: Lethal Concentration 50%	
LD50: Lethal doise 50%	
- OEL: Occupational Exposure Level	
- PEL: Predicted exposure level	
- RCRA Code: Resource Conservation and Recovery Act Code	
- REL: Recommended exposure limit	
- RID: Regulation concerning the international transport of dangerous goods by train	
- TLY: Threshold Limit Value	
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.	
- TSCA: Toxic Substances Control Act	
- TWA STEL: Short-term exposure limit	
- TWA: Time-weighted average exposure limit	
- VOC: Volatile organic Compounds	
- WHMIS: Workplace Hazardous Materials Information System.	
GENERAL BIBLIOGRAPHY: - GHS rev. 3	
- The Merck Index. 10th Edition	
- Handling Chemical Safety	
- Niosh - Registry of Toxic Effects of Chemical Substances	
- INRS - Fiche Toxicologique (toxicological sheet)	
- Patty - Industrial Hygiene and Toxicology	
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition	
- ECHA website	
- 6 NYCRR part 597	
- Cal/OSHA website	
- California Safe Drinking Water and Toxic Enforcement Act	
- EPA website	
- Hazard Comunication Standard (HCS 2012)	
- IARC website	
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act	
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"	
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".	
- New Jersey Worker and Community Right to know Act N.J.S.A.	
- NTP. 2011. Report on Carcinogens, 12th Edition.	
- OSHA website	
- Pennsylvania, Hazardous Substance List, Chapter 323	
Note for users:	
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and	
thoroughness of provided information according to each specific use of the product	1

thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.